



Exam : 642-503

Title : Securing Networks with Cisco Routers and
Switches

Ver : 10-23-07

QUESTION 1:

Please study the exhibit carefully.

```
Certkiller2 (config)#class-map type queue-threshold qt-snmpp-class
Certkiller2 (config-cmap)# match protocol snmp
Certkiller2 (config-cmap)# class-map type queue-threshold qt-telnet-class
Certkiller2 (config-cmap)# match protocol telnet
Certkiller2 (config-cmap)# class-map type queue-threshold qt-class
Certkiller2 (config-cmap)# match host-protocols
Certkiller2 (config-cmap)# exit
Certkiller2 (config)# policy-map type queue-threshold qt-policy
Certkiller2 (config-pmap)# class qt-snmpp-class
Certkiller2 (config-pmap-c)# queue-limit 50
Certkiller2 (config-pmap-c)# class qt-telnet-class
Certkiller2 (config-pmap-c)# queue-limit 50
Certkiller2 (config-pmap-c)# class qt-class
Certkiller2 (config-pmap-c)# queue-limit 150
Certkiller2 (config-pmap-c)# end
```

What traffic will be matched to the "qt-class" traffic class?

- A. all traffic matched by the "host-protocols" named access list
- B. all other traffic arriving at the interface where the "qt-policy" policy map is applied
- C. all TCP and UDP protocol ports open on the router not specifically matched
- D. all traffic other than SNMP and Telnet to the router
- E. all traffic matched by the "host-protocols" nested class map

Answer: C

QUESTION 2:

DRAG DROP

You work as a network technician at Certkiller .com. Your boss, miss Certkiller, is interested in IBNS 802.1x authentication features. Match the proper features with appropriate descriptions.

Note: not all features are used.

642-503

Options, select from these

Access VLAN

Guest VLAN

Authentication policy for a Network Access Profile (NAP)

Network Access Filters (NAFs)

Radius Authorization Components (RACs)

Restricted VLAN

Definitions

Allows logical grouping of the Network Access Devices (NADs)

Defines the RADIUS attributes downloaded to the switch upon successful authorization

Provides limited network access to clients without an 802.1x supplicant

Provides limited network access to clients with an 802.1x supplicant but failed authentication

Options, place here

Place here

Place here

Place here

Place here

Answer:

Options, select from these

Access VLAN

Authentication policy for a Network Access Profile (NAP)

Definitions

Allows logical grouping of the Network Access Devices (NADs)

Defines the RADIUS attributes downloaded to the switch upon successful authorization

Provides limited network access to clients without an 802.1x supplicant

Provides limited network access to clients with an 802.1x supplicant but failed authentication

Options, place here

Network Access Filters (NAFs)

Radius Authorization Components (RACs)

Guest VLAN

Restricted VLAN

QUESTION 3:

Please study the exhibit carefully.

```
webvpn gateway Certkiller-GW
hostname Certkiller1
ip address 10.0.1.3 port 443
http-redirect port 80
ssl trustpoint TP-self-signed-1898720763
inservice
!
webvpn context SSLVPN
title "SNRS WebVPN Page"
title-color darkseagreen
secondary-color darkgreen
secondary-text-color white
ssl encryption rc4-md5
ssl authenticate verify all
!
uri-list "MYLINKS"
heading "Quicklinks"
uri-text "Homepage" uri-value "home.certkiller.com"
uri-text "Test-URL" uri-value "certkiller.net"
uri-text "server-URL" uri-value "certkillerserver.com"
!
login-message "Please enter your credentials"
!
policy group SSL-Policy
uri-list "MYLINKS"
banner "Login Successful!"
default-group-policy SSL-Policy
gateway SNRS-GW
max-users 300
inservice
```

Which two statements are true about the configurations shown? (Choose two.)

- A. The clickable links will have a heading entitled "MYLINKS".
- B. ACS will be used for remote-user authentication by default.
- C. This is an example of a clientless configuration.
- D. The home page will have three clickable links on it.
- E. Thin client (port forwarding) has been enabled using the url-text command.

Answer: C,D

QUESTION 4:

Please study the exhibit carefully.

```
crypto ipsec transform-set MINE esp-des
!
crypto map MYMAP 10 ipsec-isakmp
set peer 172.30.5.2
set transform-set MINE
match address 101
```

What can you determine about the configuration?

- A. 3DES encryption will be used.
- B. The authentication method used between the IPsec peers is pre-shared key.
- C. This is a dynamic crypto map.
- D. Traffic matched by ACL 101 will not be encrypted.

- E. HMAC-MD5 authentication will be used.
- F. ESP tunnel mode will be used.

Answer: F

QUESTION 5:

Cisco Easy VPN Server pushes parameters such as the client internal IP address, DHCP server IP address, and WINS server IP address to the Cisco Easy VPN Remote client during which of these phases?

- A. IKE mode configuration
- B. IKE XAUTH
- C. IKE Phase 1 first message exchange
- D. IKE quick mode
- E. IKE Phase 2 last message exchange

Answer: A

QUESTION 6:

The PHDF stored in the router flash memory is required for which of these applications to function?

- A. PAM
- B. Zone-Based Firewall
- C. CPPr
- D. CoPP
- E. NBAR
- F. FPM

Answer: F

QUESTION 7:

Which three of these statements are correct regarding DMVPN configuration? (Choose three.)

- A. The GRE tunnel mode must be set to point-to-point mode: tunnel mode gre point-to-point
- B. The GRE tunnel must be associated with an IPsec profile: tunnel protection ipsec profile profile-name
- C. At the spoke routers, static NHRP mapping to the hub router is required: ip nhrp map hub-tunnel-ip-address hub-physical-ip-address
- D. The spoke routers must be configured as the NHRP servers: ip nhrp nhs spoke-tunnel-ip-address


E. If running EIGRP over DMVPN, the hub router tunnel interface must have "next hop self" enabled: ip next-hop-self eigrp AS-Number

F. If running EIGRP over DMVPN, the hub router tunnel interface must have split horizon disabled: no ip split-horizon eigrp AS-Number

Answer: B,C,F

QUESTION 8:

Please study the exhibit carefully.



Which two configuration commands are used to apply an inspect policy map for traffic traversing from the E0 or E1 interface to the S3 interface? (Choose two.)

- A. ip inspect myfwpolicy in
- B. interface E0
- C. ip inspect myfwpolicy out
- D. service-policy type inspect myfwpolicy
- E. zone-pair security test source Z1 destination Z2
- F. policy-map myfwpolicy class class-default inspect

Answer: D,E

QUESTION 9:

Which of these statements is correct regarding user setup on ACS 4.0?

- A. In the case of conflicting settings, the settings at the group level override the settings configured at the user level.
- B. The ACS PAP password cannot be used as the CHAP password also.
- C. By default, users are assigned to the default group.
- D. The username can contain characters such as "#" and "?".
- E. A user can belong to more than one group.

Answer: C

QUESTION 10:

What are two benefits of using an IPsec GRE tunnel? (Choose two.)

- A. It has less overhead than running IPsec in tunnel mode.

- B. It supports the use of dynamic crypto maps to reduce configuration complexity.
- C. It requires a more restrictive crypto ACL to provide finer security control.
- D. It allows dynamic routing protocol to run over the tunnel interface.
- E. It allows IP multicast traffic.

Answer: D,E

QUESTION 11:

Please study the exhibit carefully.

```
aaa new-model
aaa authentication login default group tacacs+
aaa authorization auth-proxy default group tacacs+
aaa accounting auth-proxy default start-stop group tacacs+
enable password Test-y23
ip auth-proxy name pxy http
ip auth-proxy auth-proxy-banner
interface Ethernet0/1
 ip address 192.168.1.1 255.255.255.0
 ip auth-proxy pxy
 no ip http server
 tacacs-server host 192.168.123.14
 tacacs-server key cisco
! Output omitted
```

Why is the Cisco IOS Firewall authentication proxy not working?

- A. HTTP server and AAA authentication for the HTTP server is not enabled.
- B. The AAA method lists used for authentication proxy should be named "pxy" rather than "default" to match the authentication proxy rule name.
- C. Cisco IOS authentication proxy only supports RADIUS and not TACACS+.
- D. The aaa authentication auth-proxy default group tacacs+ command is missing in the configuration.
- E. The router local username and password database is not configured.

Answer: A

QUESTION 12:

When verifying Cisco IOS IPS operations, when should you expect Cisco IOS IPS to start loading the signatures?

- A. immediately after you configure the ip ips sdf builtin command
- B. when the SMEs are put into active state using the ip ips name rule-name command
- C. after traffic reaches the interface with Cisco IOS IPS enabled
- D. after you configure a Cisco IOS IPS rule in the global configuration
- E. when the first Cisco IOS IPS rule is enabled on an interface
- F. immediately after you configure the ip ips sdf location flash:filename command

Answer: E

QUESTION 13:

When troubleshooting site-to-site IPsec VPN on Cisco routers, you see this console message:

```
%CRYPTO-6-IKMP_SA_NOT_OFFERED: Remote peer %15i responded with attribute [chars] not offered or changed
```

Which configuration should you verify?

- A. the IPsec transform set
- B. the DH group
- C. the crypto map
- D. the crypto ACL
- E. the pre-shared key
- F. the ISAKMP policies

Answer: F

QUESTION 14:

When you implement 802.1x authentication on the ACS, which two configurations are performed under the ACS System Configuration? (Choose two.)

- A. Global Authentication Setup
- B. Users
- C. RACs
- D. Logging
- E. NAPs
- F. Groups

Answer: A,D

QUESTION 15:

Which two statements are true regarding classic Cisco IOS Firewall configurations? (Choose two.)

- A. You can apply the IP inspection rule in the outbound direction on the untrusted

interface.

- B. For temporary openings to be created dynamically by Cisco IOS Firewall, you must apply the IP inspection rule to the trusted interface.
- C. You can apply the IP inspection rule in the inbound direction on the trusted interface.
- D. For temporary openings to be created dynamically by Cisco IOS Firewall, the access list for the returning traffic must be a standard ACL.
- E. For temporary openings to be created dynamically by Cisco IOS Firewall, the inbound access list on the trusted interface must be an extended ACL.

Answer: A,C

QUESTION 16:

ACS administrators use which TCP port to access the Cisco ACS web interface?

- A. 2002
- B. 80
- C. 443
- D. 8080
- E. 22
- F. 127

Answer: A

QUESTION 17:

Please study the exhibit carefully.

```
aaa new-model
aaa authentication dot1x default group radius
aaa authentication network default group radius
aaa accounting dot1x default start-stop group radius
aaa accounting system default start-stop group radius
radius-server host 10.1.1.1 auth-port 1812 acct-port 1813
radius-server key certkiller300
```

Which optional AAA or RADIUS configuration command is used to support 802.1x guest VLAN functionality?

- A. aaa authentication dot1x default group radius
- B. radius-server host 10.1.1.1 auth-port 1812 acct-port 1813
- C. aaa accounting dot1x default start-stop group radius
- D. aaa accounting system default start-stop group radius
- E. aaa authorization network default group radius

Answer: E

QUESTION 18:

DRAG DROP

You work as a network technician at Certkiller .com. Your boss, miss Certkiller, is interested in NFP (Network Foundation Protection) features. Match the proper features with appropriate descriptions.

Options, select from these

FPM (Flexible Packet Matching)

CoPP (Control Plane Policing)

CPP (Control plane protection)

Definitions

Applies to data plane traffic

Options,place here

Place here

Applies to all (aggregated) control-plane traffic

Place here

Applies to a control-plane sub-if, example, host or transit or cef-exception

Place here

Answer:

Definitions

Applies to data plane traffic

Options,place here

FPM (Flexible Packet Matching)

Applies to all (aggregated) control-plane traffic

CoPP (Control Plane Policing)

Applies to a control-plane sub-if, example, host or transit or cef-exception

CPP (Control Plane Protection)

QUESTION 19:

DRAG DROP

You work as a network technician at Certkiller .com. Your boss, miss Certkiller, is interested in Cisco IOS Firewall features. Match the proper features with appropriate descriptions.

Note: not all features are used.

Options, select from these

- Application firewall
- Firewall ACL Hypass
- Transparent firewall
- Zone-based Firewall (ZBF)

- Auth proxy
- Granular Protocol Inspection (GPI)
- Virtual firewall

Definitions

- Allows network administrators to specify TCP or UDP ports using the PAM table
- Allows network administrators to apply specific security policies on a per-user basis
- Allows inspection of HTTP and instant messaging traffic
- Allows the Cisco IOS Firewall to permit packets based on inspection sessions instead of ACL
- New method of configuring Cisco IOS Firwall using class-maps and policy-maps

Options,place here

- Place here
- Place here
- Place here
- Place here
- Place here

Answer:

Options, select from these

- Transparent firewall

Options,place here

- Virtual firewall

Definitions

- Allows network administrators to specity TCP or UDP ports using the PAM table
- Allows network administrators to apply specific security policies on a per-user basis
- Allows inspection of HTTP and instant messaging traffic
- Allows the Cisco IOS Firewall to permit packets based on inspection sessions instead of ACL
- New method of configuring Cisco IOS Firwall using class-maps and policy-maps

Options,place here

- Granular Protocol Inspection (GPI)
- Auth-proxy
- Application firewall
- Firewall ACL bypass
- Zone-based Firewall (ZBF)

QUESTION 20:

DRAG DROP

You work as a network technician at Certkiller .com. Your boss, miss Certkiller, is interested in ACS 4.0 component functions. Match the proper components with appropriate functions.

Options, select from these

Postoure Validation Policy

NAFs

NAPs

RACs

Functions

Options,place here

To define flexible network device restriction policies

Place here

To classify an access request and map it to a profile

Place here

To ensure that every endpoint confirms to the security policy before being granted access to the network (NAC)

Place here

To send VLAN assignment information to teh NAD

Place here

Answer:

Functions

Options,place here

To define flexible network device restriction policies

NAFs

To classify an access request and map it to a profile

NAPs

To ensure that every endpoint confirms to the security policy before being granted access to the network (NAC)

Posture Validation Policy

To send VLAN assignment information to teh NAD

RACs

QUESTION 21:

Please study the exhibit carefully.

Given that the fa0/1 interface is the trusted interface, what could be a reason for users on the trusted inside networks not to be able to successfully establish outbound HTTP connections?

```
Certkiller2 #show ip inspect interfaces
Interface Configuration
Interface FastEthernet0/1
  Inbound inspection rule is FWRULE
    tcp alert is on audit-trail is on timeout 300
    ftp alert is on audit-trail is on timeout 300
  Outgoing inspection rule is not set
  Inbound access list is 104
  Outgoing access list is not set.
```

```
Certkiller2 #show run
<output omitted>
!ACL 104
access-list 104 permit icmp any any
access-list 104 permit tcp 10.0.1.0 0.0.0.255 any eq ftp
!
```

- A. The FWRULE inspection policy is not configured correctly.
- B. ACL 104 is denying the outbound HTTP traffic.
- C. ACL 104 is denying the return HTTP traffic.
- D. The FWRULE inspection policy is not inspecting HTTP traffic.
- E. The outgoing ACL on the fa0/1 interface is not set.
- F. The outgoing inspection rule on the fa0/1 interface is not set.

Answer: B

QUESTION 22:

When you add NADs as AAA clients in the ACS, which three parameters are configured for each AAA client? (Choose three.)

- A. the EAP type
- B. the AAA server IP address
- C. the UDP ports to use for communications with the NADs
- D. the AAA protocol to use for communications with the NADs
- E. the shared secret key
- F. the NAD IP address

Answer: D,E,F

QUESTION 23:

When you configure Cisco IOS WebVPN, you can use the port-forward command to enable which function?

- A. thin client
- B. CIFS
- C. Cisco Secure Desktop
- D. OWA

- E. full-tunnel client
- F. web-enabled applications

Answer: A

QUESTION 24:

Which Cisco IOS command will trigger the router to request certificates from the CA for the router RSA key pair?

- A. crypto pki trustpoint CA-Name
- B. enrollment url http://CA-Name:80
- C. crypto pki enroll CA-Name
- D. crypto pki authenticate CA-Name
- E. crypto key zeroize rsa
- F. crypto key generate rsa

Answer: C

QUESTION 25:

When configuring FPM, what should be the next step after the PHDFs have been loaded?

- A. Define a stack of protocol headers.
- B. Define a traffic policy.
- C. Define a class map of type "access-control" for classifying packets.
- D. Save the PHDFs to startup-config.
- E. Reload the router.
- F. Define a service policy.

Answer: A

QUESTION 26:

Please study the exhibit carefully.

Which two statements are correct? (Choose two.)

```
ip ips name certkillerISP
!
interface Gigabite Ethernet0/1
ip address 10.1.1.16 255.255.255.0
ip ips MYIPS in
!
```

- A. SDEE alert messages will be enabled.
- B. syslog alert messages will be enabled.
- C. The basic signatures (previously known as 128MB.sdf) will be used if the built-in signatures fail to load.
- D. The built-in signatures will be used.

E. Cisco IOS IPS will fail-open.

Answer: D,E

QUESTION 27:

When you implement IBNS (802.1x authentication), what is defined using the Tunnel-Private-Group-ID (81) RADIUS attribute?

- A. the shared secret key
- B. the NAP
- C. the NAF
- D. the VLAN name
- E. the ACL name
- F. the EAP type

Answer: D

QUESTION 28:

If you enable all the authentication protocols under the Global Authentication Setup in Cisco ACS, how can you select a specific EAP type to use for 802.1x authentication?

- A. When you configure the NAF, you can specify the particular EAP type to use.
- B. When you configure the NAP authentication policy, you can specify the particular EAP type to use.
- C. When you configure the RAC, you can specify the particular EAP type to use.
- D. When you configure the NAP authorization policy, you can specify the particular EAP type to use.
- E. When you configure the user group, you can specify the particular EAP type to use.
- F. When you configure the user, you can specify the particular EAP type to use.

Answer: B

QUESTION 29:

DRAG DROP

You work as a network technician at Certkiller .com. Your boss, miss Certkiller, is interested in debug commands which can be used to troubleshoot the WebVPN functions. Match the proper comman with appropriate functions.

Note: not all commands are used.

642-503

Options, select from these

debug webvpn webservice

debug webvpn dns

debug webvpn port forward

debug webvpn aaa

Definitions

Users having problems with the Thin client operations

Users getting unable to connect to server error message when trying to access the http://www.certkiller.com url

Users having problems logging into WebVPN

Options,place here

Place here

Place here

Place here

Answer:

Options, select from these

debug webvpn webservice

Definitions

Users having problems with the Thin Client operations

Users getting unable to connect to server error message when trying to access the http://www.certkiller.com url

Users having problems logging into WebVPN

debug webvpn port-forward

debug webvpn dns

debug webvpn aaa

QUESTION 30:

Please study the exhibit carefully.
What will result from this zone-based firewall configuration?

```
class-map type inspect match-all myprotocols
  match protocol http
  match protocol dns
!
policy-map type inspect nyfwpolicy
  class type inspect myprotocols
  inspect
!
zone security private
zone security public
!
interface fastethernet 0/0
  zone-member security private
!
interface fastethernet 0/1
  zone-member security public
!
zone-pair security priv-to-pub source private destination public
  service-policy type inspect myfwpolicy
```

- A. All traffic from the private zone to the public zone will be permitted but not inspected.
- B. All traffic from the private zone to the public zone will be permitted and inspected.
- C. Only HTTP and DNS traffic from the private zone to the public zone will be permitted and inspected.
- D. All traffic from the private zone to the public zone will be dropped.
- E. Only HTTP and DNS traffic from the public zone to the private zone will be permitted and inspected.
- F. All traffic from the public zone to the private zone will be permitted but not inspected.

Answer: D

QUESTION 31:

When you enter the switch(config)#aaa authentication dot1x default group radius command on a Cisco Catalyst switch, the Cisco IOS parser returns with the "invalid input detected" error message. What can be the cause of this error?

- A. You must use the dot1x system-auth-control command first to globally enable 802.1x.
- B. You must define the RADIUS server IP address first, using the switch(config)#radius-server host ip-address command.
- C. You must enter the aaa new-model command first.
- D. The local option is missing in the command.
- E. The method-list name is missing in the command.

Answer: C

QUESTION 32:

DRAG DROP

You work as a network technician at Certkiller .com. Your boss, miss Certkiller, is interested in Cisco IOS IPS commands and features. Match the proper command and features with appropriate descriptions.

Options, select from these

SDF

SMEs

SDEE

Post Office Protocol

Definitions

Has definitions for each signature it contains

Protocol used to send IPS event messages to the management station

No longer supported in latest current Cisco IOS releases

Used to load the SDF and to scan signatures

Options,place here

Place here

Place here

Place here

Place here

Answer:

Definitions

Has definitions for each signature it contains

Protocol used to send IPS event messages to the management station

No longer supported in latest current Cisco IOS releases

Used to load the SDF and to scan signatures

Options,place here

SDF

SDEE

Post Office Protocol

SMEs

QUESTION 33:

Please study the exhibit carefully.

What additional configuration is required for the Cisco IOS Firewall to reset the TCP connection if any peer-to-peer, tunneling, or instant messaging traffic is detected over HTTP?

```
appfw policy-name Certkillerpolicy
application http
strict-http action reset alarm
content-length maximum 1 action reset alarm
content-type-verification match-req-rsp action reset alarm
max-header-length request 1 response 1 action reset alarm
max-uri-length 1 action reset alarm
request-method rfc put action reset alarm
transfer-encoding type default action reset alarm
!
ip inspect name firewall appfw mypolicy
ip inspect name firewall http
!
interface FastEthernet0/0
ip inspect firewall in
```


- A. the port-misuse default action reset alarm command in the HTTP application firewall policy configuration
- B. the service default action reset command in the HTTP application firewall policy configuration
- C. the PAM configuration for mapping the peer-to-peer, tunneling, and instant messaging TCP ports to the HTTP application
- D. the ip inspect name firewall im, ip inspect name firewall p2p, and ip inspect name firewall tunnel commands
- E. class-map configuration for matching peer-to-peer, tunneling, and instant messaging traffic over HTTP, and a policy map specifying the reset action

Answer: A

QUESTION 34:

SIMULATION

Network topology exhibit



You work as a network technician at Certkiller .com. Certkiller .com has a main office in Bonn and a Satellite office in Leipzig. Please refer to the network topology exhibit.

You are required to configure CBAC on the Certkiller 3 route.

Previously access list 100 has already been built. It has been applied to fa0/0.

In particular:

- * configure CBAC to inspect web traffic to the corporate server Certkiller B
- * configure CBAC to inspect FTP traffic to the corporate server Certkiller B
- * configure CBAC to permit ICMP packets from any source to any destination inbound to the local router fa0/1 interface.
- * configure CBAC to permit EIGRP packets from any source to any destination inbound to the local router fa0/1 interface.
- * Apply the IP inspect rule on the fa0/0 interface
- * enable logging of CBAC session information
- * configure the Certkiller A server IP address

The enable password is Certkiller

Answer:


Explanation:

```
Certkiller 3(config)#logging on
Certkiller 3(config)#logging 10.0.2.12
Certkiller 3(config)#ip inspect audit-trail
Certkiller 3(config)#no ip inspect alert-off
Certkiller 3(config)#ip inspect name outbound http java-list 99
Certkiller 3(config)#ip inspect name outbound ftp
Certkiller 3(config)#ip inspect name outbound icmp
Certkiller 3(config)#access-list 99 permit host 172.26.26.50
Certkiller 3(config)#int fasteth0/0
Certkiller 3(config-if)#ip inspect outbound in
Certkiller 3(config)#access-list 101 permit icmp any any echo-reply
```

```
Certkiller 3(config)#access-list 101 permit icmp any any time-exceeded
Certkiller 3(config)#access-list 101 permit icmp any any packet-too-big
Certkiller 3(config)#access-list 101 permit icmp any any traceroute
Certkiller 3(config)#access-list 101 permit icmp any any unreachable
Certkiller 3(config)#access-list 101 permit eigrp any any
Certkiller 3(config)#access-list 101 deny ip any any
Certkiller 3(config)#int fasteth0/1
Certkiller 3(config-if)#ip access-group 101 in
```

QUESTION 35:

Network topology exhibit



Certkiller 1 configuration exhibit:

```
Certkiller1# show running config
crypto ipsec transform-set MINE esp-des
asp-md5-hmac
!
crypto map MYMAP 10 ipsec-isakmp
set peer 172.30.2.2
set transform-set MINE
match address 110
!
interface Ethernet 0/1
ip address 172.30.1.2 255.255.255.0
no ip directed-broadcast
crypto map MYMAP
!
access-list 110 permit tcp 10.0.1.0
0.0.0.255 10.0.2.0 0.0.0.255
!
router eigrp 1
network 10.0.0.0
network 172.30.0.0
```

Certkiller 2 configuration exhibit:

```
Certkiller2 # show running config
crypto ipsec transform-set MINE esp-des
esp-md5-hmac
!
crypto map MYMAP 10 ipsec-isakmp
set peer 172.30.1.2
set transform-set MINE
match address 101
!
interfaces Ethernet 0/1
ip address 172.30.2.2 255.255.255.0
no ip directed-broadcast
crypto map MYMAP
!
access-list 101 permit tcp 10.0.2.0
0.0.0.255 10.0.1.0 0.0.0.255
!
router eigrp 2
network 10.0.0.0
network 172.30.0.0
```

Refer to the exhibits. Why is the IPsec site-to-site VPN between Router Certkiller 1 and Router Certkiller 2 not working?

- A. The crypto maps are missing the authentication method configuration.
- B. The crypto ACLs of the two routers do not match.
- C. The crypto ACLs are not permitting the routing protocol traffic between Router Certkiller 1 and Router Certkiller 2.
- D. Neither router has a route in its routing table to reach the other protected subnet.
- E. The IPsec SA lifetime has not been configured.
- F. The crypto maps default to transport mode, need to specify tunnel mode in the crypto maps.

Answer: D

QUESTION 36:

Which three configurations are required to enable the Cisco IOS Firewall to inspect a user-defined application which uses TCP ports 8000 and 8001? (Choose three.)

- A. policy-map user-10 class user-10 inspect
- B. int {type|number} ip inspect name test in
- C. ip inspect name test appfw user-10
- D. ip inspect name test user-10
- E. ip port-map user-10 port tcp 8000 8001 description "TEST PROTOCOL"
- F. access-list 101 permit tcp any any eq 8000 access-list 101 permit tcp any any eq 8001 class-map user-10 match access-group 101

Answer: B,D,E

QUESTION 37:

Please study the exhibit carefully.

Why is the Total Active Signatures count zero?

```
Certkiller1#show ip ips all
Configured SDF Locations:
flash:/128MB.sdf
Builtin signatures are enabled but not loaded
Last successful SDF load time: 00:50:03 UTC Aug 22 2006
IPS fail closed is disabled
Fastpath ips is enabled
Quick run mode is enabled
Event notification through syslog is enabled
Event notification through SDEE is enabled
Total Active Signatures: 0
Total Inactive Signatures:0
IPS Rule Configuration
IPS name test
Certkiller1#
```

- A. IPS has not been enabled on an interface yet.
- B. The flash:/128MB.sdf needs to be merged with the built-in signatures first.
- C. The 128MB.sdf file in flash is corrupted.
- D. IPS is in fail-closed mode.
- E. IPS is in fail-open mode.

Answer: A

QUESTION 38:

When you implement 802.1x authentication, the RACs configured under the Shared Profile Components in the ACS are referenced by which other ACS component?

- A. group setup
- B. user setup
- C. the posture-validation policy of the NAP
- D. the authentication policy of the NAP
- E. the authorization policy of the NAP
- F. the NDG

Answer: E

QUESTION 39:

Cisco IOS Zone-Based Firewall uses which of these to identify a service or application from traffic flowing through the firewall?

- A. deep packet inspection
- B. PAM table
- C. application layer inspection
- D. CEF table

- E. extended access list
- F. NBAR

Answer: B

QUESTION 40:

When you configure a site-to-site IPsec VPN tunnel, which configuration must be the exact reverse (mirror image) of the other IPsec peer?

- A. IPsec transform set
- B. crypto map
- C. pre-shared key
- D. ISAKMP policy
- E. static route
- F. crypto ACL

Answer: F

QUESTION 41:

When you implement Cisco IOS WebVPN on a Cisco router using a self-signed certificate, you notice that the router is not generating a self-signed certificate. What should you check to troubleshoot this issue?

- A. Verify the ip http server configuration.
- B. Verify the WebVPN group policy configuration.
- C. Verify the AAA authentication configuration.
- D. Verify the ip http secure-server configuration.
- E. Verify that the WebVPN gateway is inservice.
- F. Verify the WebVPN context configuration.

Answer: E

QUESTION 42:

Please study the exhibit carefully.

What additional configuration is required to enable split tunneling?

```
aaa new-model
aaa authentication login userlist group radius local
aaa authorization network grouplist group radius local
enable password XXXX
!
username disco password 0 cisco
!
crypto isakmp policy 1
hash md5
authentication pre-share
group 2
!
crypto isakmp identity hostname
!
crypto isakmp client configuration group cisco
key cisco
dns 10.2.2.2 10.2.2.3
wins 10.6.6.6
domain cisco.com
pool green
!
crypto ipsec transform-set dessha esp-des esp-sha-hmac
!
crypto dynamic-map mode 1
set transform-set dessha
!
crypto map mode client authentication list userlist
crypto map mode isakmp authorization list grouplist
crypto map mode client configuration address respond
crypto map mode 1 ipsec-isakmp dynamic mode
!
interface FastEthernet0/0
ip address 10.6.1.8 255.255.0.0
crypto map mode
!
ip local pool green 192.168.2.1 192.168.2.10
!
ip route 0.0.0.0 0.0.0.0 10.6.0.1
!
access-list 199 permit ip 192.168.1.0 0.0.0.255 any
access-list 199 permit ip 192.168.3.0 0.0.0.255 any
!
radius-server host 192.168.1.1 auth-port 1645 acct-port 1646 key XXXX
```

- A. the reverse-route command under "crypto isakmp client configuration group cisco"
- B. the reverse-route command under "crypto dynamic-map mode 1"
- C. the include-local-lan command under "crypto isakmp client configuration group cisco"
- D. the include-local-lan under "crypto dynamic-map mode 1"
- E. the acl 199 command under "crypto isakmp client configuration group cisco"
- F. the match address 199 command under "crypto dynamic-map mode 1"

Answer: E

QUESTION 43:

What are the three authentication methods that you can use during IKE Phase 1? (Choose three.)

- A. Kerberos
- B. DH
- C. pre-shared key
- D. RSA signature
- E. AAA or Local Authentication
- F. RSA encrypted nonce

Answer: C,D,F

QUESTION 44:

Refer to the partial classic Cisco IOS Firewall configuration shown in the exhibit. Which three are the correct missing configuration commands? (Choose three.)

```
ip inspect name myfw ftp timeout 3600
ip inspect name myfw http java-list 51 timeout 30
ip inspect name myfw udp timeout 15
ip inspect name myfw tcp timeout 3600
!
interface Ethernet0
!Inside trusted interface
ip address 172.16.139.1 255.255.255.0
1 _____
2 _____
!
interface Ethernet1
!Outside untrusted interface
ip address 172.16.140.1 255.255.255.0
3 _____
!
access-list 51 permit host 192.168.1.1
access-list 51 deny any

access-list 101 permit tcp 172.16.139.0 0.0.0.255 any
access-list 101 permit udp 172.16.139.0 0.0.0.255 any
access-list 101 permit icmp 172.16.139.0 0.0.0.255 any
access-list 101 deny ip any any
!
access-list 111 deny ip 172.16.139.0 0.0.0.255 any
access-list 111 permit icmp any 172.16.139.0 0.0.0.255 echo
access-list 111 permit icmp any 172.16.139.0 0.0.0.255 echo-reply
access-list 111 deny ip any any
```

- A. 2=ip access-group 101 in
- B. 1=ip access-group 51 in
- C. 1=ip inspect myfw in
- D. 3=ip inspect myfw in
- E. 2=ip inspect myfw out
- F. 3=ip access-group 111 in

Answer: A,C,F

QUESTION 45:

Referring to a DMVPN hub router tunnel interface configuration, what can happen if the

ip nhrp map multicast dynamic command is missing on the tunnel interface?


- A. The NHRP mappings at the spoke routers will be incorrect.
- B. The IPsec peering between the hub router and the spoke router will fail.
- C. The NHRP request and response between the spoke router and hub router will fail.
- D. The NHRP mappings at the hub router will be incorrect.
- E. The GRE tunnel between the hub router and the spoke router will be down.
- F. The dynamic routing protocol between the hub router and the spoke router will fail.

Answer: F

QUESTION 46:

Please study the exhibit carefully.

When you configure DHCP snooping, which ports should be configured as trusted ?




- A. port E only
- B. port A only
- C. ports B and C
- D. ports A, B, C, and E
- E. ports A, B, and C
- F. ports B, C, and E

Answer: E

QUESTION 47:

Refer to the DMVPN topology diagram in the exhibit. Which two statements are correct? (Choose two.)



- A. The hub router Certkiller 1 needs to have EIGRP split horizon disabled.
- B. At the Certkiller 4 router, the next hop to reach the 192.168.0.0/24 network is 172.17.0.1.
- C. The spoke routers Certkiller 2 and Certkiller 4 act as the NHRP servers for resolving the remote spoke physical interface IP address.
- D. At the Certkiller 2, the next hop to reach the 192.168.1.0/24 network is 172.17.0.1.
- E. Before a spoke-to-spoke tunnel can be built, the spoke router needs to send an NHRP query to the hub to resolve the remote spoke router physical interface IP address.
- F. At the Certkiller 4, the next hop to reach the 192.168.2.0/24 network is 10.0.0.1.

Answer: A,E

QUESTION 48:

What does this command do?

```
Certkiller 3(config)# ip port-map user-1 port tcp 4001
```

- A. enables the Cisco IOS Firewall to inspect TCP port 4001 as part of the ip inspect name xxx TCP inspection rule
- B. enables NBAR to recognize a user-defined application on TCP port 4001
- C. enables application firewall inspection on a user-defined application that is mapped to TCP port 4001
- D. defines a user application in the PAM table where the user-defined application is called "user-1" and that application is mapped to TCP port 4001

Answer: D

QUESTION 49:

Which two commands are used to only allow SSH traffic to the router Eth0 interface and deny other management traffic (BEEP, FTP, HTTP, HTTPS, SNMP, Telnet, TFTP) to the router interfaces? (Choose two.)

- A. interface eth0
- B. service-policy type port-filter input policy-name
- C. control-plane host
- D. line vty 0 5 transport input ssh
- E. policy-map type port-filter policy-name
- F. management-interface eth0 allow ssh

Answer: C,F

QUESTION 50:

When configuring ACS 4.0 Network Access Profiles (NAPs), which three things can be used to determine how an access request is classified and mapped to a profile? (Choose three.)

- A. the protocol types
- B. Network Access Filters (NAFs)
- C. RADIUS VSAs
- D. the authentication method
- E. RADIUS Authorization Components (RACs)
- F. advance filtering

Answer: A,B,F

QUESTION 51:

Please study the exhibit carefully.
Why is auth-proxy not working?

```

aaa new-model
aaa authentication login default group radius
aaa authentication network default group radius
!
radius-server host 10.1.1.1
radius-server key cisco123
!
ip http server
ip http authentication aaa
!
ip auth-proxy auth-cache-time 60
ip auth-proxy name HQU http
!
interface e0
ip address 10.1.1.210 255.255.255.0
ip auth-proxy HQU

```


- A. The ip auth-proxy HQU interface configuration command is missing the in direction option.
- B. The local username and password database is not configured.
- C. AAA accounting is not enabled.
- D. The aaa authorization command is not correct.
- E. HTTPS is not enabled on the router.
- F. The AAA authentication method-list is not configured.

Answer: D

QUESTION 52:

SIMULATION

Network topology exhibit



You work as a network technician at Certkiller .com. Certkiller .com has a server Certkiller A connected to their network infrastructure through a switch Certkiller A. Certkiller .com is using VLANs to improve security, nevertheless you notice that there is a CAM table overflow attack in progress through port fa0/12.. The attacker is spoofing MAC addresses through the Certkiller A switch.

You are required to reconfigure the switch so that the attacker has no change of overflowing the CAM table. If more than one MAC address is learned on a port, the port

should shut down.

The Certkiller A enable password is Certkiller

Answer:

Explanation:

```
Certkiller A# config t
```

```
Certkiller A(config)#interface fast0/12
```

```
Certkiller A(config-if)# switchport port-security
```

```
Certkiller A(config-if)# switchport port-security maximum 1
```

```
Certkiller A(config-if)# switchport port-security violation
```

```
shutdown
```

QUESTION 53:

A new Certkiller switch has been installed and you wish to secure it. Which Cisco Catalyst IOS command can be used to mitigate a CAM table overflow attack?

- A. switch(config-if)# port-security maximum 1
- B. switch(config)# switchport port-security
- C. switch(config-if)# port-security
- D. switch(config-if)# switchport port-security maximum 1
- E. switch(config-if)# switchport access
- F. switch(config-if)# access maximum 1

Answer: D

Explanation:

Enabling and Configuring Port Security:

Beginning in privileged EXEC mode, follow these steps to restrict input to an interface by limiting and identifying MAC addresses of the stations allowed to access the port:

	Command	Purpose
Step 1	configure terminal	Enter global configuration mode.
Step 2	interface <i>interface-id</i>	Specify the interface to configure and enter interface configuration mode.
Step 3	switchport mode access	Set the interface mode as access; an interface in the default mode (dynamic desirable) cannot be configured as a secure port.
Step 4	switchport port-security	Enable port security on the interface.
Step 5	switchport port-security maximum <i>value</i>	(Optional) Set the maximum number of secure MAC addresses for the interface. The range is 1 to 132; the default is 1.

To ensure that only a single station's MAC address is allowed on a given port, specify the value of the "switchport port-security maximum" command to 1. This will safeguard against CAM overflow attacks.


Reference:

http://www.cisco.com/en/US/products/hw/switches/ps5206/products_configuration_guide_chapter09186a00801c

QUESTION 54:

SIMULATION

The following diagram displays a portion of the Certkiller network:



You work for the Certkiller .com, which has a server connected to their infrastructure through a switch named Houston. Although Certkiller .com uses VLANs for security, an attacker is trying to overflow the CAM table by sending out spoofed MAC addresses through a port on the same switch as the server. Your task is to configure the switch to protect the switch from a CAM table overflow attack. For purposes of this test, we will assume that the attacker is plugged into port Fa0/12. The topology is pictured in the exhibit. The enable password for the switch

is Certkiller . The following passwords have been assigned to the Houston switch:

Console passwords: california

VTY lines 0-4 password: city

Enable passwords: Certkiller

Start the simulation by clicking on the host.

Answer:

Explanation:

```
Switch1(config)# interface fastethernet0/12
```

```
Switch1(config-if)# switchport mode access
```

```
Switch1(config-if)# switchport port-security
```

```
Switch1(config-if)# switchport port-security maximum 1
```

```
Switch1(config-if)# end
```

Enabling and Configuring Port Security:

Beginning in privileged EXEC mode, follow these steps to restrict input to an interface by limiting and identifying MAC addresses of the stations allowed to access the port:

	Command	Purpose
Step 1	configure terminal	Enter global configuration mode.
Step 2	interface <i>interface-id</i>	Specify the interface to configure and enter interface configuration mode.
Step 3	switchport mode access	Set the interface mode as access; an interface in the default mode (dynamic desirable) cannot be configured as a secure port.
Step 4	switchport port-security	Enable port security on the interface.
Step 5	switchport port-security maximum <i>value</i>	(Optional) Set the maximum number of secure MAC addresses for the interface. The range is 1 to 132; the default is 1.

To ensure that only a single station's MAC address is allowed on a given port, specify the value of the "switchport port-security maximum" command to 1. This will safeguard against CAM overflow attacks.

Reference:

http://www.cisco.com/en/US/products/hw/switches/ps5206/products_configuration_guide_chapter09186a00801c

QUESTION 55:

You want to increase the security of a newly installed switch. Which Cisco Catalyst IOS command is used to mitigate a MAC spoofing attack?

A. switch(config-if)# port-security mac-address 0000.ffff.aaaa

- B. switch(config)# switchport port-security mac-address 0000.ffff.aaaa
- C. switch(config-if)# switchport port-security mac-address 0000.ffff.aaaa
- D. switch(config)# port-security mac-address 0000.ffff.aaaa
- E. switch(config-if)# mac-address 0000.ffff.aaaa
- F. switch(config)# security mac-address 0000.ffff.aaaa

Answer: C

Explanation:

You can use the port security feature to restrict input to an interface by limiting and identifying MAC addresses of the workstations that are allowed to access the port. When you assign secure MAC addresses to a secure port, the port does not forward packets with source addresses outside the group of defined addresses. If you limit the number of secure MAC addresses to one and assign a single secure MAC address, the workstation attached to that port is assured the full bandwidth of the port.

If a port is configured as a secure port and the maximum number of secure MAC addresses is reached, when the MAC address of a workstation attempting to access the port is different from any of the identified secure MAC addresses, a security violation occurs. If a workstation with a secure MAC that is address configured or learned on one secure port attempts to access another secure port, a violation is flagged.

After you have set the maximum number of secure MAC addresses on a port, the secure addresses are included in an address table in one of these ways:

You can configure all secure MAC addresses by using the switchport port-security mac-address mac_address interface configuration command.

You can allow the port to dynamically configure secure MAC addresses with the MAC addresses of connected devices.

You can configure a number of addresses and allow the rest to be dynamically configured.

Reference:

http://www.cisco.com/en/US/products/hw/switches/ps708/products_configuration_guide_chapter09186a00800d

Note: there is no ability to use "copy running-config startup-config" or "write memory", so each solution should use the "end" command in config mode to save the current configuration.

QUESTION 56:

The security administrator for Certkiller Inc. is working on defending the network against SYN flooding attacks. Which of the following are tools to protect the network from TCP SYN attacks?

- A. Route authentication
- B. Encryption
- C. ACLs
- D. TCP intercept
- E. None of the above.

Answer: D

Explanation:

The TCP intercept feature implements software to protect TCP servers from TCP SYN-flooding attacks, which are a type of denial-of-service attack.

A SYN-flooding attack occurs when a hacker floods a server with a barrage of requests for connection. Because these messages have unreachable return addresses, the connections cannot be established. The resulting volume of unresolved open connections eventually overwhelms the server and can cause it to deny service to valid requests, thereby preventing legitimate users from connecting to a web site, accessing e-mail, using FTP service, and so on.

The TCP intercept feature helps prevent SYN-flooding attacks by intercepting and validating TCP connection requests. In intercept mode, the TCP intercept software intercepts TCP synchronization (SYN) packets from clients to servers that match an extended access list. The software establishes a connection with the client on behalf of the destination server, and if successful, establishes the connection with the server on behalf of the client and knits the two half-connections together transparently. Thus, connection attempts from unreachable hosts will never reach the server. The software continues to intercept and forward packets throughout the duration of the connection. The number of SYNs per second and the number of concurrent connections proxied depends on the platform, memory, processor, and other factors

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1835/products_configuration_guide_chapter09186a00800c

QUESTION 57:

Which of the following IOS commands will you advise the Certkiller trainee technician to use when setting the timeout for router terminal line?

- A. exec-timeout minute [seconds]
- B. line-timeout minute [seconds]
- C. timeout console minute [seconds]
- D. exec-time minutes [seconds]

Answer: A

Explanation:

The exec timeout command prevents unauthorized users from misusing abandoned sessions (for instance if the network administrator went on vacation and left an enabled login session active on his desktop system). There is a trade-off here between security (shorter timeouts) and usability (longer timeouts). Check your local policies and operational needs to determine the best value. In most cases, this should be no more than 10 minutes. To configure the timeout values, perform the following steps:
router(config)# line INSTANCE

```
router(config-line)# exec-timeout $(EXEC_TIMEOUT)
```

```
router(config-line)# exit
```

Reference: http://www.cisco.com/warp/public/793/access_dial/comm_server.html

QUESTION 58:

The Certkiller network is implementing IBNS. In a Cisco Identity-Based Networking Service (IBNS) implementation, the endpoint that is seeking network access is known as what?

- A. Host
- B. Authentication
- C. PC
- D. Authentication server
- E. Client
- F. Supplicant

Answer: F

Explanation:

In IBNS, the supplicant is the end device that is seeking network access. The supplicant is a software component on the user workstation that answers a challenge from the authenticator. Supplicant functionality may also be implemented on network devices to authenticate to upstream devices.

Reference: Securing Networks with Cisco Routers and Switches (SNRS) Courseware Page 3-30.

QUESTION 59:

A new IBNS system is being installed in the Certkiller network. The Cisco Identity-Based Networking Services (IBNS) solution is based on which two standard implementations? (Choose two.)

- A. TACACS+
- B. RADIUS
- C. 802.11
- D. 802.1x
- E. 802.1q
- F. IPSec

Answer: B, D

Explanation:

The Cisco IBNS solution is based on standard RADIUS and 802.1X implementations. It interoperates with all IETF authentication servers that comply with these two standards. Cisco has enhanced the Cisco Secure ACS to provide a tight integration across all Cisco

switches.

Reference: Securing Networks with Cisco Routers and Switches (SNRS) Courseware
Page 3-24.

QUESTION 60:

You wish to configure 802.1X port control on your switch. Which three keywords are used with the dot1x port-control command? (Choose three.)

- A. enable
- B. force-authorized
- C. force-unauthorized
- D. authorized
- E. unauthorized
- F. auto

Answer: B, C, F

Explanation:

To enable manual control of the authorization state on a port, use the "dot1x port-control" command. To return to the default setting, use the no form of this command.

```
dot1x port-control {auto | force-authorized | force-unauthorized}
```

```
no dot1x port-control {auto | force-authorized | force-unauthorized}
```

Syntax Description:

auto	Enables 802.1X authentication on the interface and causes the port to transition to the authorized or unauthorized state based on the 802.1X authentication exchange between the switch and the client.
force-authorized	Disables 802.1X authentication on the interface and causes the port to transition to the authorized state without any authentication exchange required. The port transmits and receives normal traffic without 802.1X-based authentication of the client.
force-unauthorized	Denies all access through the specified interface by forcing the port to transition to the unauthorized state, ignoring all attempts by the client to authenticate. The switch cannot provide authentication services to the client through the interface.

Reference:

http://www.cisco.com/en/US/products/hw/switches/ps4324/products_command_reference_chapter09186a00803

QUESTION 61:

The Certkiller network has rolled out an 802.1X based system. In an 802.1x implementation, the authenticator acts as a gateway to which device?

- A. Host

- B. Authenticator
- C. PC
- D. Authentication server
- E. Client
- F. Supplicant

Answer: D

Explanation:

The table below outlines the definitions for the authentication server and the authenticator:

802.1X Terminology	
Term	Definition
Authenticator	(Referred to as the "authenticator") entity at one end of a point-to-point LAN segment that enforces host authentication. The authenticator is independent of the actual authentication method and functions only as a pass-through for the authentication exchange. It communicates with the host, submits the information from the host to the authentication server, and authorizes the host when instructed to do so by the authentication server.
Authentication server	Entity that provides the authentication service for the authenticator P.A.E. It checks the credentials of the host P.A.E and then notifies its client, the authenticator P.A.E, whether the host P.A.E is authorized to access the LAN/switch services.

Reference:

http://www.cisco.com/en/US/products/hw/switches/ps708/products_configuration_guide_chapter09186a0080206

QUESTION 62:

The Certkiller network is using an 802.1X implementation. In an 802.1x implementation, the supplicant directly connects to, and obtains network access permission through which device?

- A. Host
- B. Authenticator
- C. PC
- D. Authentication server
- E. Client
- F. Supplicant

Answer: B

Explanation:

In Identity Based Networking Services, the supplicant is the end device that is seeking network access. The supplicant is a software component on the user workstation that answers a challenge from the authenticator.

The authenticator is the entity at one end of a point-to-point LAN segment that enforces host authentication. The authenticator is independent of the actual authentication method and functions only as a pass-through for the authentication exchange. It communicates with the host, submits the information from the host to the authentication server, and authorizes the host when instructed to do so by the authentication server.

Reference: Securing Networks with Cisco Routers and Switches (SNRS) Courseware Page 3-30.

QUESTION 63:

Which two are typical Layer 2 attacks? (Choose two.)

- A. MAC spoofing
- B. CAM table overflow
- C. Route poisoning
- D. DHCP Starvation
- E. ARP Starvation
- F. Spam
- G. Worm Hole

Answer: A, B

Explanation:

Layer 2 network attacks include all of the following:

CAM Table Overflow

VLAN Hopping

Spanning-Tree Protocol Manipulation

MAC Spoofing Attack

Private VLAN Attacks

DHCP Starvation

Cisco Discovery Protocol

VLAN Trunking Protocol

IEEE 802.1x

MAC Spoofing Attack

MAC spoofing attacks involve the use of a known MAC address of another host to attempt to make the target switch forward frames destined for the remote host to the network attacker. By sending a single frame with the other host's source Ethernet address, the network attacker overwrites the CAM table entry so that the switch forwards packets destined for the host to the network attacker. Until the host sends traffic it will not receive any traffic. When the host sends out traffic, the CAM table entry is rewritten once more so that it moves back to the original port.

CAM Table Overflow:

The CAM table in a switch contains information such as the MAC addresses available on a given physical port of a switch, as well as the associated VLAN parameters. When a Layer 2 switch receives a frame, the switch looks in the CAM table for the destination MAC address. If an entry exists for the MAC address in the CAM table, the switch forwards the frame to the port designated in the CAM table for that MAC address. If the MAC address does not exist in the CAM table, the switch forwards the frame out every port on the switch, effectively acting like a hub. If a response is seen, the switch updates the CAM table.

Reference:

http://www.cisco.com/en/US/netsol/ns340/ns394/ns171/ns128/networking_solutions_white_paper09186a008014

QUESTION 64:

You want to increase the security levels at layer 2 within the Certkiller switched LAN. Which three are typical Layer 2 attack mitigation techniques? (Select three)

- A. Switch security
- B. Port security
- C. ARP snooping
- D. DHCP snooping
- E. Port snooping
- F. 802.1x authentication

Answer: B, D, F

Explanation:

Network Attack Mitigation:

Use the port security commands to mitigate MAC-spoofing attacks. The port security command provides the capability to specify the MAC address of the system connected to a particular port. The command also provides the ability to specify an action to take if a port-security violation occurs. However, as with the CAM table-overflow attack mitigation, specifying a MAC address on every port is an unmanageable solution.

Hold-down timers in the interface configuration menu can be used to mitigate ARP spoofing attacks by setting the length of time an entry will stay in the ARP cache. However, hold-down timers by themselves are insufficient. Modification of the ARP cache expiration time on all end systems would be required as well as static ARP entries. Even in a small network this approach does not scale well. One solution would be to use private VLANs to help mitigate these network attacks.

Another solution that can be used to mitigate various ARP-based network exploits is the use of DHCP snooping along with Dynamic ARP Inspection (DAI). These Catalyst feature validate ARP packets in a network and permit the interception, logging, and discarding of ARP packets with invalid MAC address to IP address bindings.

DHCP Snooping provides security by filtering trusted DHCP messages and then using these messages to build and maintain a DHCP snooping binding table. DHCP Snooping considers DHCP messages originating from any user facing port that is not a DHCP

server port or an uplink to a DHCP server as untrusted. From a DHCP Snooping perspective these untrusted, user-facing ports should not send DHCP server type responses such as DHCPOffer, DHCPAck, or DHCPNak. Untrusted DHCP messages are messages received from outside the network or firewall. The DHCP snooping binding table contains the MAC address, IP address, lease time, binding type, VLAN number, and interface information corresponding to the local untrusted interfaces of a switch; it does not contain information regarding hosts interconnected with a trusted interface. An untrusted interface is an interface configured to receive messages from outside the network or firewall. A trusted interface is an interface that is configured to receive only messages from within the network. The DHCP snooping binding table can contain both dynamic as well as static MAC address to IP address bindings.

Another effective mitigation strategy is to deploy 802.1x on access switches and wireless access points to ensure that all access to the network infrastructure requires authentication. Consider deploying PEAP for use with wireless LANs.

Reference:

http://www.cisco.com/en/US/netsol/ns340/ns394/ns171/ns128/networking_solutions_white_paper09186a008014

QUESTION 65:

The Certkiller security administrator is in charge of creating a security policy for the company. Which two statements about the creation of a security policy are true? (Choose two)

- A. It helps Chief Information Officers determine the return on investment of network security at Certkiller Inc.
- B. It defines how to track down and prosecute policy offenders at Certkiller Inc.
- C. It helps determine which vendor security equipment or software is better than others.
- D. It clears the general security framework so you can implement network security at Certkiller Inc.
- E. It provides a process to audit existing network security at Certkiller Inc.
- F. It defines which behavior is and is not allowed at Certkiller Inc.

Answer: E, F

Explanation:

Reasons to create a network security policy:

1. Provides a process to audit existing network security
2. Provides a general security framework for implementing network security
3. Defines which behavior is and is not allowed
4. Often helps determine which tools and procedures are needed for the organization
5. Helps communicate consensus among a group of key decision-makers and defines responsibilities of users and administrators
6. Defines a process for handling network security incidents
7. Enables global security implementation and enforcement

8. Creates a basis for legal action if necessary

Reference: Managing Cisco Network Security, Cisco Press, page 43

QUESTION 66:

The Certkiller routers have all been upgraded to a firewall feature set IOS. What are three main components of the Cisco IOS Firewall feature set? (Choose three)

- A. Context-based Access Control
- B. Port security
- C. Authentication proxy
- D. Authentication, authorization, and accounting
- E. Intrusion Prevention System
- F. Neighbor router authentication

Answer: A, C, E

Explanation:

The Cisco IOS firewall feature set contains the following features:

Context-Based Access Control (CBAC)-CBAC creates temporary openings in access lists at firewall interfaces. These openings are created when specified traffic exits your internal network through the firewall. The openings allow returning traffic (that would normally be blocked) and additional data channels to enter your internal network back through the firewall. The traffic is allowed back through the firewall only if the traffic is part of the same session as the original traffic that triggered CBAC when exiting through the firewall.

Cisco IOS Intrusion Prevention System (IPS)-The Cisco IOS IPS feature restructures the existing Cisco IOS Intrusion Detection System (IDS), allowing customers to choose to load the default, built-in signatures or to load a Signature Definition File (SDF) called attack-drop.sdf onto the router. The attack-drop.sdf file contains 118 high-fidelity Intrusion Prevention System (IPS) signatures, providing customers with the latest available detection of security threats.

Cisco IOS Firewall Authentication Proxy-Authentication proxy provides dynamic, per-user authentication and authorization, authenticating users against industry standard TACACS+ and RADIUS authentication protocols. Per-user authentication and authorization of connections provide more robust protection against network attacks.

Reference:

http://www.cisco.com/en/US/products/ps5854/prod_configuration_guide09186a00802c9587.html

QUESTION 67:

Router CK1 is configured with the IOS firewall feature set to prevent TCP based attacks. How many incomplete connections must this router have by default before TCP Intercept will start dropping incomplete connections?

- A. 500

- B. 1100
- C. 700
- D. 900
- E. 200
- F. 250

Answer: B

Explanation:

Once the number of incomplete connections (TCP SYN) reaches 1100, TCP Intercept will start deleting incomplete sessions (oldest session first, by default). Configure the incomplete session threshold with the "ip tcp intercept max-incomplete high (number)" command.

QUESTION 68:

Which of the following represents the behavior of the CBAC aggressive mode in a Cisco IOS firewall?

- A. Delete all half-open session
- B. Re-initiate half open session
- C. Complete all half open sessions, make the full open session
- D. Delete half-open session as needed to accommodate new connection requests
- E. All of the above, based on configuration

Answer: D

Explanation:

A TCP SYN attack occurs when an attacking source host generates TCP SYN packets with random source addresses and sends them in rapid succession to a victim host. The victim destination host sends a SYN ACK back to the random source address and adds an entry to the connection queue. Since the SYN ACK is destined for an incorrect or nonexistent host, the acknowledgment is never completed and the entry remains in the connection queue until a timer expires. The connection queue fills up and legitimate users cannot use TCP services. However, with CBAC, TCP packets flow from the outside only in response to traffic sent from the inside. The attacking host can't get its packets through, and the attack does not succeed. In addition, by inspecting inbound on the external interface (interface serial 0 in the example above), CBAC can account for half-open connections through the firewall and begin closing those half-open connections in an aggressive mode. The firewall will calm down once the number of half-open connections settles down to a user-defined value.

QUESTION 69:

What OSI layers can CBAC filter on? Select all that apply.

- A. Layer 4
- B. Layer 3
- C. Layer 2
- D. Layer 7
- E. Layer 5

Answer: A, B, D

Explanation:

Access lists can filter traffic based on layer 3 and layer 4 information, while CBAC can filter traffic based on layer 3, 4, and 7 (application layer) information.

QUESTION 70:

Router CK1 has been upgraded with the Cisco firewall IOS. Which of the following cannot be configured on a router unless the IOS Firewall feature set is installed? (Select all that apply)

- A. PAM
- B. Authentication Proxy
- C. IDS
- D. CBAC

Answer: A, B, C, D

Explanation:

CBAC, PAM, IDS, Authentication Proxy are the four main components of the Cisco IOS Firewall and cannot be configured until the IOS Firewall feature set is installed on the router. The following table describes these features in more detail:

Context-based Access Control	"Configuring Context-Based Access Control"	<p>Context-based Access Control (CBAC) examines not only network layer and transport layer information, but also examines the application-layer protocol information (such as FTP information) to learn about the state of TCP and UDP connections. CBAC maintains connection state information for individual connections. This state information is used to make intelligent decisions about whether packets should be permitted or denied, and dynamically creates and deletes temporary openings in the firewall.</p> <p>CBAC also generates real-time alerts and audit trails. Enhanced audit trail features use SYSLOG to track all network transactions. Real-time alerts send SYSLOG error messages to central management consoles upon detecting suspicious activity. Using CBAC inspection rules, you can configure alerts and audit trail information on a per-application protocol basis. CBAC is only available in the Cisco IOS Firewall feature set.</p>
Cisco IOS Firewall Intrusion Detection System	"Configuring Cisco IOS Firewall Intrusion Detection System"	<p>The Cisco IOS Firewall Intrusion Detection System (IDS) acts as an in-line intrusion detection sensor, watching packets and sessions as they flow through the router, scanning each to match any of the IDS signatures. When it detects suspicious activity, it responds before network security can be compromised and logs the event through Cisco IOS syslog. The network administrator can configure the IDS system to choose the appropriate response to various threats. When packets in a session match a signature, the IDS system can be configured to:</p> <ul style="list-style-type: none"> • Send an alarm to a syslog server or a Cisco NetRanger Director (centralized management interface) • Drop the packet • Reset the TCP connection

Authentication Proxy	"Configuring Authentication Proxy"	The Cisco IOS Firewall authentication proxy feature allows network administrators to apply specific security policies on a per-user basis. Previously, user identity and related authorized access was associated with a user's IP address, or a single security policy had to be applied to an entire user group or sub network. Now, users can be identified and authorized on the basis of their per-user policy, and access privileges tailored on an individual basis are possible, as opposed to general policy applied across multiple users.
Port to Application Mapping	"Configuring Port to Application Mapping"	Port to Application Mapping (PAM) is a feature of Cisco IOS Firewall. PAM allows you to customize TCP or UDP port numbers for network services or applications. PAM uses this information to support network environments that run services using ports that are different from the registered or well-known ports associated with an application. The information in the PAM table enables CBAC supported services to run on nonstandard ports.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1835/products_configuration_guide_chapter09186a00800c

QUESTION 71:

Router CK1 is being used to prevent Denial of Service attacks on the Certkiller network. Which three thresholds does CBAC on the Cisco IOS Firewall provide against DoS attacks? (Choose three)

- A. The number of half-open sessions based upon time
- B. The total number of half-open TCP or UDP sessions
- C. The number of fully open sessions based upon time
- D. The number of half-open TCP-only sessions per host
- E. The total number of fully open TCP or UDP sessions
- F. The number of fully open TCP-only sessions per host

Answer: A, B, D

Explanation:

Enhanced denial-of-service detection and prevention defends networks against popular attack modes, such as SYN (synchronize/start) flooding, port scans, and packet injection, by inspecting packet sequence numbers in TCP connections. If numbers are not within expected ranges, the router drops suspicious packets. When the router detects unusually high rates of new connections, it issues an alert message, and subsequently drops half-open TCP connection state tables. This prevents system resource depletion.

When the Cisco IOS Firewall detects a possible attack, it tracks user access by source or destination address and port pairs. It also details the transaction, creating an audit trail. The CBAC process can be configured to monitor these half opened sessions based on the total number within a given time frame, the total number at any given point, or the total number per any individual host. When the number of existing half-open sessions exceeds the max-incomplete high number, CBAC deletes half-open sessions as required to accommodate new connection requests. The software continues to delete half-open requests until the number of existing half-open sessions drops below max-incomplete low number.

Reference:

http://www.cisco.com/en/US/products/sw/secursw/ps1018/prod_bulletin09186a008010e040.html

QUESTION 72:

The Certkiller network is concerned about SPAM and wants to use IOS tools to prevent SPAM attacks. By default, how many message recipients must an email have for the IOS Firewall to consider it a spam attack?

- A. 250
- B. 500
- C. 100
- D. 25
- E. 5000
- F. 50000
- G. None of the above

Answer: A

Explanation:

By default, the Cisco IOS Firewall will fire an alarm for a spam attack if an email contains 250 or more recipients.

To specify the number of recipients in a mail message over which a spam attack is suspected, use the "ip audit smtp" global configuration command. To set the number of recipients to the default setting, use the no form of this command.

ip audit smtp spam number-of-recipients

Syntax Description

spam	Specifies a threshold beyond which the Cisco IOS Firewall IDS alarms on spam e-mail.
<i>number-of-recipients</i>	Integer in the range of 1-65535 that designates the maximum number of recipients in a mail message before a spam attack is suspected. Use with the spam keyword. The default is 250 recipients.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1835/products_command_reference_chapter09186a00800

c

QUESTION 73:

The security administrator at Certkiller is seeing a large number of half opened TCP sessions. What are half open TCP sessions?

- A. Sessions that were denied.
- B. Sessions that have not reached the established state.
- C. Sessions where the three-way handshake has been completed.
- D. Sessions where the firewall detected return traffic.

Answer: B

Explanation:

An unusually high number of half-open sessions (either absolute or measured as the arrival rate) could indicate that a denial-of-service attack is occurring. For TCP, "half-open" means that the session has not reached the established state. For UDP, "half-open" means that the firewall has detected traffic from one direction only.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1831/products_command_reference_chapter09186a00800d

QUESTION 74:

What command configures the amount of time CBAC will wait for a TCP session to become established before dropping the connection in the state table?

- A. ip inspect global syn-establish (seconds)
- B. ip inspect tcp global syn-time (seconds)
- C. ip inspect global tcp syn (seconds)
- D. ip inspect tcp synwait-time (seconds)
- E. None of the above

Answer: D

Explanation:

Use the IOS Firewall global configuration mode command ip inspect tcp synwait-time (seconds) command to set the CBAC timeout value for TCP session establishment. The default is 30 seconds.

QUESTION 75:

You have been tasked with setting up a new router with CBAC. How do you configure the CBAC global UDP idle session timeout?

- A. ip inspect udp-session-timeout (seconds)

- B. ip inspect udp-idle (seconds)
- C. ip inspect udp-timeout (seconds)
- D. ip inspect udp idle-time (seconds)

Answer: D

Explanation:

Determine the global UDP idle session state table timeout value with the ip inspect udp idle-time (seconds) command. This global value (along with the global tcp idle timeout) can be overridden on a per-protocol basis.

QUESTION 76:

You have been tasked with setting up a new Certkiller router with CBAC. How do you set the threshold of half-open sessions CBAC will allow per minute before deleting them?

- A. ip inspect one-minute incomplete (number)
- B. ip inspect one-minute (number)
- C. ip inspect one-minute high (number)
- D. ip inspect one-minute high incomplete (number)
- E. ip inspect max-incomplete minute high (number)

Answer: C

Explanation:

The "ip inspect one-minute high (number)" command will set the number of new, half-open connections per minute CBAC will allow before deleting them. The default is 500 per minute.

QUESTION 77:

You are setting up a new Certkiller router with CBAC. Which of the following commands will alter the CBAC DNS timeout timer to 10 seconds?

- A. ip inspect dns-server-timeout 10
- B. ip inspect dns-server-timer 10
- C. ip inspect dns-timeout 10
- D. ip inspect dns-timer 10

Answer: C

Explanation:

To configure the time CBAC will keep a DNS session open in the state table, use the global configuration command ip inspect dns-timeout (seconds). The default is five seconds.

QUESTION 78:

You are setting up a new Certkiller router with CBAC. If CBAC is configured to inspect telnet traffic on an interface, how should outbound telnet traffic be configured in any ACL's?

- A. Outbound telnet should be permitted in any acl's
- B. Outbound telnet should be denied in any acl's
- C. Telnet should not be referenced at all in the acl
- D. Outbound telnet should be denied only if inbound telnet is allowed

Answer: A

Explanation:

With CBAC, the ACL's need to allow the initial outbound traffic. If the traffic is not allowed outbound access, CBAC will not have a chance to monitor and restrict the return session traffic.

QUESTION 79:

CBAC has been configured on router CK1 to increase the security of the Certkiller network. CBAC intelligently filters TCP and UDP packets based on which protocol-session information?

- A. Network layer
- B. Transport layer
- C. Data-link
- D. Application layer
- E. Presentation layer
- F. Session layer
- G. Physical layer

Answer: D

Explanation:

Context-based Access Control (CBAC) in Cisco IOS Firewall is an advanced traffic filtering technology that intelligently filters transmission control protocol (TCP) and user datagram protocol (UDP) packets to determine whether they contain malicious viruses or worms. CBAC can be configured to permit specified TCP and UDP traffic through a firewall only when the connection is initiated from within the network to be protected. Without CBAC, traffic filtering is limited to access list implementations that examine packets at the network layer or at the transport layer. CBAC examines not only these but also the application-layer protocol information to learn about the state of a TCP or UDP session.

QUESTION 80:

John and Kathy are working on configuring the IOS firewall together. They are figuring out what CBAC uses for inspection rules to configure on a per-application protocol basis. Which one of these is the correct one?

- A. ODBC filtering
- B. Tunnel, transport models, or both
- C. Alerts and audit trails
- D. Stateful failover
- E. None of the above

Answer: C

Explanation:

CBAC also generates real-time alerts and audit trails. Enhanced audit trail features use SYSLOG to track all network transactions. Real-time alerts send SYSLOG error messages to central management consoles upon detecting suspicious activity. Using CBAC inspection rules, you can configure alerts and audit trail information on a per-application protocol basis.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1835/products_configuration_guide_chapter09186a00800c

QUESTION 81:

You are the security administrator for Certkiller and you need to know what CBAC does on the Cisco IOS Firewall. Which one of these is the best answer?

- A. Creates specific security policies for each user at Certkiller Inc.
- B. Provides additional visibility at intranet, extranet, and Internet perimeters at Certkiller Inc.
- C. Protects the network from internal attacks and threats at Certkiller Inc.
- D. Provides secure, per-application access control across network perimeters at Certkiller Inc.

Answer: D

Explanation:

Context-based Access Control (CBAC) examines not only networklayer and transportlayer information, but also examines the application-layer protocol information (such as FTP information) to learn about the state of TCP and UDP connections. CBAC maintains connection state information for individual connections. This state information is used to make intelligent decisions about whether packets should be permitted or denied, and dynamically creates and deletes temporary openings in the firewall.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1831/products_configuration_guide_chapter09186a00800d

QUESTION 82:

By default, how many half-open sessions need to be in the state table before CBAC will begin to delete the half-open sessions?

- A. 500
- B. 250
- C. 1000
- D. 2000
- E. 100
- F. 50

Answer: A

Explanation:

By default, CBAC will begin to delete half-open sessions when there are 500 in the state table. It will keep deleting half-open sessions until the minimum half-open sessions threshold is met (default is 400).

QUESTION 83:

The authentication proxy feature has been configured on one of the Certkiller routers. What does authentication proxy on the Cisco IOS Firewall do?

- A. Creates specific authorization policies for each user with Cisco Secure ACS, dynamic, per-user security and authorization
- B. Provides additional visibility at intranet, extranet, and Internet perimeters
- C. Creates specific security policies for each user with Cisco Secure ACS, dynamic, per-user authentication and authorization
- D. Provides secure, per-application access control across network perimeters

Answer: C

Explanation:

The Cisco IOS Firewall authentication proxy feature allows network administrators to apply specific security policies on a per-user basis. Previously, user identity and related authorized access was associated with a user's IP address, or a single security policy had to be applied to an entire user group or sub network. Now, users can be identified and authorized on the basis of their per-user policy, and access privileges tailored on an individual basis are possible, as opposed to general policy applied across multiple users. With the authentication proxy feature, users can log in to the network or access the Internet via HTTP, and their specific access profiles are automatically retrieved and applied from a CiscoSecureACS, or other RADIUS, or TACACS+ authentication server.

The user profiles are active only when there is active traffic from the authenticated users.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1831/products_configuration_guide_chapter09186a00800d

QUESTION 84:

You have been tasked with configuring authentication proxy on one of the Certkiller routers. Which command is required to specify the authorization protocol for authentication proxy?

- A. auth-proxy group tacacs+
- B. aaa auth-proxy default group tacacs+
- C. authorization auth-proxy default group tacacs+
- D. aaa authorization auth-proxy default group tacacs+
- E. aaa authorization auth-proxy group tacacs+
- F. aaa authorization auth-proxy default group

Answer: D

Explanation:

To configure authentication proxy for accounting, begin by using the following commands in global configuration mode:

	Command	Purpose
Step 1	Router(config)# <code>aaa new-model</code>	Enables AAA.
Step 2	Router(config)# <code>aaa authentication login default group tacacs+</code>	Defines the list of authentication methods at login.
Step 3	Router(config)# <code>aaa authorization auth-proxy default group tacacs+</code>	Uses the auth-proxy keyword to enable authentication proxy for AAA methods.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1834/products_feature_guide09186a0080080348.html

QUESTION 85:

The Certkiller administrator is working on configuring the authentication proxy feature. Which of the following best describes the authentication proxy feature of the Cisco IOS?

- A. Use a general policy applied across multiple Certkiller Inc. users
- B. Use a single security policy that is applied to an entire user group or subnet at Certkiller Inc.
- C. Apply specific security policies on a per-user basis at Certkiller Inc.

D. Keep the Certkiller Inc. user profiles active even where there is no active traffic from the authenticated users.

Answer: C

Explanation:

The Cisco IOS Firewall authentication proxy feature allows network administrators to apply specific security policies on a per-user basis. Previously, user identity and related authorized access was associated with a user's IP address, or a single security policy had to be applied to an entire user group or sub network. Now, users can be identified and authorized on the basis of their per-user policy, and access privileges tailored on an individual basis are possible, as opposed to general policy applied across multiple users. With the authentication proxy feature, users can log in to the network or access the Internet via HTTP, and their specific access profiles are automatically retrieved and applied from a CiscoSecureACS, or other RADIUS, or TACACS+ authentication server. The user profiles are active only when there is active traffic from the authenticated users.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1831/products_configuration_guide_chapter09186a00800d

QUESTION 86:

You are configuring the authentication feature on a new Certkiller router. Which of the following correctly sets the IOS Firewall authentication-proxy idle timer to 20 minutes?

- A. ip auth-proxy auth-cache 20
- B. ip auth-proxy auth-time 20
- C. ip auth-proxy auth-cache-time 20
- D. ip auth-proxy idle 20
- E. ip auth-proxy idle timer 20

Answer: C

Explanation:

Use the global configuration mode command "ip auth-proxy auth-cache-time (minutes)" to determine the acceptable idle period for users authenticated through the IOS Firewall before they must re-authenticate.

QUESTION 87:

You are configuring the authentication feature on a new Certkiller router. Which of the following configures an authentication proxy rule for the IOS Firewall?

- A. ip inspect-proxy name proxynome http
- B. ip auth-proxy name proxynome http

- C. ip auth-rule proxynome http
- D. ip proxy-name proxynome http

Answer: B

Explanation:

Create an authentication proxy rule with the global configuration mode command ip auth-proxy name (name) http. Apply the proxy rule to an interface to force users to authenticate through the firewall.

QUESTION 88:

The authentication proxy feature has been configured on one of the Certkiller routers. Where are access profiles stored with the authentication proxy features of the Cisco IOS Firewall?

- A. PIX Firewall
- B. Cisco router
- C. Cisco VPN Concentrator
- D. Cisco Secure ACS authentication server

Answer: D

Explanation:

With the authentication proxy feature, users can log in to the network or access the Internet via HTTP, and their specific access profiles are automatically retrieved and applied from a CiscoSecureACS, or other RADIUS, or TACACS+ authentication server. The user profiles are active only when there is active traffic from the authenticated users.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1831/products_configuration_guide_chapter09186a00800d

QUESTION 89:

Refer to the output of a "sh ip auth-proxy cache" command issued on a Certkiller router below. Which port is being used by the client?

```
CK2 # sh ip auth-proxy cache
```

```
Authentication Proxy Cache
```

```
Client Name aauser, Client IP 10.0.2.12, Port 2636, timeout 5, Time Remaining 3, state ESTAB
```

Based on this information, which port is being used by the client?

- A. 1645
- B. 1646
- C. 1812
- D. 2636

- E. 2640
- F. 8080

Answer: D

Explanation:

Use the "show ip auth-proxy" to display either the authentication proxy entries or the running authentication proxy configuration. Use the cache keyword to list the host IP address, the source port number, the timeout value for the authentication proxy, and the state for connections using authentication proxy. If authentication proxy state is HTTP_ESTAB, the user authentication was successful. In this example, the client was established using port 2636.

QUESTION 90:

How does a user on the Certkiller LAN trigger the authentication proxy after the idle timer has expired?

- A. The proxy authenticates the user
- B. The user initiates another HTTP session
- C. The user enters a new username and password
- D. The user enters a valid username and password
- E. None of the above

Answer: B

Explanation:

How the Authentication Proxy Works:

When a user initiates an HTTP session through the firewall, the authentication proxy is triggered. The authentication proxy first checks to see if the user has been authenticated. If a valid authentication entry exists for the user, the connection is completed with no further intervention by the authentication proxy. If no entry exists, the authentication proxy responds to the HTTP connection request by prompting the user for a username and password.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1831/products_configuration_guide_chapter09186a00800d

QUESTION 91:

Router CK1 has been configured for authentication proxy. What is the default idle time of an enabled IOS Firewall authentication proxy?

- A. 5 seconds
- B. 50 seconds
- C. 5 minutes

- D. 60 minutes
- E. 3600 minutes
- F. 1 Day

Answer: D

Explanation:

To set the authentication proxy idle timeout value (the length of time an authentication cache entry, along with its associated dynamic user ACL, is managed after a period of inactivity), use the "ipauth-proxy auth-cache-time" command in global configuration mode. To set the default value, use the no form of this command.

<i>min</i>	Specifies the length of time in minutes that an authentication cache entry, along with its associated dynamic user ACL, is managed after a period of inactivity. Enter a value in the range 1 to 2,147,483,647. The default value is 60 minutes.
------------	--

ip auth-proxy auth-cache-time min

Syntax Description

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1831/products_command_reference_chapter09186a00800d

QUESTION 92:

A new Certkiller router is being configured for IDS services. Choose the two types of signature implementations that the IOS Firewall IDS can detect. (Choose two.)

- A. Atomic
- B. Dynamic
- C. Regenerative
- D. Cyclical
- E. Compound
- F. Complex

Answer: A, E

Explanation:

The Cisco IOS firewall IDS can detect atomic and compound signatures:

Atomic signatures detect simple patterns (ie: attempt on a specific host or within a single packet) while compound signatures detect complex patterns (ie: attack on multiple hosts, over extended time periods with multiple packets).

QUESTION 93:

On router R2, the "show ip ips config" command was issued as shown below:

```
R2#sh ip ips conf
Configured SDF Locations:
 flash:my-signatures.sdf
Builtin signatures are enabled but not loaded
Last successful SDF load time: 03:55:17 UTC Mar 2 2002
IDS fail closed is enabled
Fastpath ips is enabled
Quick run mode is enabled
Event notification through syslog is enabled
Event notification through Net Dlieghto is disabled
Event notification through SDEE is disabled
Total Active Signatures: 183
Total Inactive Signatures: 0
Signature 1107:0 disable
PostOffice:HostID:0 OrgID:0 Msg dropped:0
:Curr Event Buf Size:0 Configured:100
Post Office is not enabled - No connections are active
IDS Rule Configuration
IPS name SECURIPS
Interface Configuration
Interface FastEthernet0/1
Inbound IPS rule is SECURIFS
Outgoing IPS rule is not set
```

Refer to the exhibit. Given the output of the show ip ips configuration command, how many signatures are active?

- A. 0
- B. 50
- C. 83
- D. 100
- E. 183
- F. 1107
- G. None of the above.

Answer: E

Explanation:

From the output shown above the total number of active signatures that this router is monitoring is 183.

Note: The 1107:0 signature is a specific signature ID, which has been manually disabled in this example. This value does not refer to the total number of signatures.

QUESTION 94:

Select two issues that you should consider when implementing IOS Firewall IDS.
(Choose two)

- A. The memory usage
- B. The number of DMZs

- C. The signature coverage
- D. The number of router interfaces
- E. The signature length

Answer: A, C

Explanation:

The performance impact of intrusion detection will depend on the configuration of the signatures, the level of traffic on the router, the router platform, and other individual features enabled on the router such as encryption, source route bridging, and so on. Enabling or disabling individual signatures will not alter performance significantly; however, signatures that are configured to use Access Control Lists will have a significant performance impact.

Because this router is being used as a security device, no packet will be allowed to bypass the security mechanisms. The IDS process in the Cisco IOS Firewall router sits directly in the packet path and thus will search each packet for signature matches. In some cases, the entire packet will need to be searched, and state information and even application state and awareness must be maintained by the router.

For auditing atomic signatures, there is no traffic-dependent memory requirement, but the memory usage should be monitored with IDS. For auditing compound signatures, CBAC allocates memory to maintain the state of each session for each connection. Memory is also allocated for the configuration database and for internal caching.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1835/products_configuration_guide_chapter09186a00800c

QUESTION 95:

To prevent against attacks on your network, you have enabled your router for Intrusion Detection Services. What are the three actions that the IOS Firewall IDS router may perform when a packet, or a number of packets in a session, match a signature? (Choose three)

- A. Forward packet to the Cisco IDS Host Sensor for further analysis
- B. Send an alarm to the Cisco IDS Directory or Syslog server
- C. Send an alarm to Cisco Secure ACS
- D. Set the packet reset flag and forward the packet through
- E. Drop the packet immediately
- F. Return the packet to the sender

Answer: B, D, E

Explanation:

The Cisco IOS firewall IDS can be configured to react to suspected malicious traffic in any combination of three ways:

1) Send an alarm - The Cisco IOS firewall IDS can be configured to send an alarm to a

syslog server or a centralized management system such as the Cisco Secure IDS Director, the IDS Management Console (IDS MC), the Cisco IDS Event Viewer, or the Cisco Secure Policy Manager (CSPM).

2) Drop the packet - The Cisco IOS firewall can dynamically create an access list that allows the system to drop the incoming packet.

3) Reset the TCP connection - The Cisco IOS firewall can forward packets to both source and destination with the RESET flag set.

Reference: CCSP student guide, p.283

QUESTION 96:

A packet is passing through a Certkiller IOS IDS system. Which module is audited first when packets enter an IOS Firewall IDS and match a specific audit rule?

- A. TCP
- B. ICMP
- C. IP
- D. Application level
- E. UDP

Answer: C

Packets going through the interface that match the audit rule are audited by a series of modules, starting with IP; and then either ICMP, TCP, or UDP (as appropriate); and finally, the Application level.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1830/products_feature_guide_chapter09186a00800881c0.html

QUESTION 97:

The IOS Firewall is capable of taking certain types of action in cases where a packet or a number of packets in a session, match a signature. What are these actions? (Choose all that apply)

- A. It will drop the packet immediately
- B. It can return the packet to the sender
- C. It can forward packet to the Cisco Ids Host Sensor for further analysis
- D. It will the Cisco IDS Director or Syslog server by sending an alarm to it
- E. It will send an alarm to Cisco Secure ACS
- F. It can set the packets' reset flag and forward the packet through

Answer: A, D, F

Explanation:

The Cisco IOS firewall IDS can be configured to react to suspected malicious traffic in any combination of three ways:

- 1) Send an alarm - The Cisco IOS firewall IDS can be configured to send an alarm to a syslog server or a centralized management system such as the Cisco Secure IDS Director, the IDS Management Console (IDS MC), the Cisco IDS Event Viewer, or the Cisco Secure Policy Manager (CSPM).
 - 2) Drop the packet - The Cisco IOS firewall can dynamically create an access list that allows the system to drop the incoming packet.
 - 3) Reset the TCP connection - The Cisco IOS firewall can forward packets to both source and destination with the RESET flag set.
- Reference: CCSP student guide, p.283
-

QUESTION 98:

A new Cisco IDS system has been installed to protect the Certkiller network from outside attacks. What kind of signatures trigger on a single packet? (Choose one)

- A. Regenerative
- B. Cyclical
- C. Atomic
- D. Dynamic
- E. Compound
- F. None of the above

Answer: C

Explanation:

An atomic attack represents exploits contained within a single packet. For example, the "ping of death" attack is a single, abnormally large ICMP packet.

QUESTION 99:

A perimeter router configured for TCP Intercept is being installed in the Certkiller network to prevent TCP based attacks. What is the default mode TCP Intercept operates in?

- A. Intercept
- B. Aggressive
- C. 3-way
- D. Responsive
- E. Watch

Answer: A

Explanation:

TCP Intercept can be in either intercept mode or passive watch mode. In intercept mode, each TCP SYN packet will be intercepted and responded to on behalf of the server it is protecting. With passive watch mode, TCP Intercept monitors the connection to the

server to make sure the connection becomes complete. If the server cannot complete the connection within a configurable time period, TCP Intercept will send a reset packet to the server, clearing up the server's resources.

QUESTION 100:

You are configuring a new Certkiller router to prevent SPAM attacks. Which of the following commands correctly sets the IOS Firewall IDS spam threshold?

- A. ip audit smtp spam 500
- B. ip audit smtp spam 500 notify
- C. ip audit smtp name spam 500
- D. ip audit ids spam 500
- E. None of the above

Answer: A

Explanation:

Set the threshold at which a spam alarm is triggered for the number of recipients in an email with the "ip audit smtp spam (number)" command.

QUESTION 101:

While logged into a Certkiller router, which of the following commands can be used to verify your IOS Firewall IDS configuration? (Select all that apply)

- A. show ip audit attack
- B. show ip audit statistics
- C. show ip audit all
- D. show ip audit tcp
- E. show ip audit info

Answer: B, C

Explanation:

To verify your IOS Firewall IDS configuration there are six options with the show ip audit command: all, configuration, interfaces, name, sessions, and statistics.

QUESTION 102:

While logged into a Certkiller router, which of the following commands specifies that the IOS Firewall IDS engine drops packets and resets TCP connections for information signatures?

- A. ip audit name audit1 info attack drop reset
- B. ip audit name audit1 info action drop reset

- C. ip audit name audit1 info sig action drop reset
- D. ip audit name audit1 sig info drop reset
- E. None of the above

Answer: B

Explanation:

Specify the action the IOS Firewall IDS engine should take (reset, drop, alarm) for informational and attacks signatures with the ip audit name command.

QUESTION 103:

Which of the following commands disables an IOS Firewall IDS signature from being scanned in a Certkiller Cisco router?

- A. ip audit ids attack signature (sig#) disable
- B. ip audit ids signature (sig#) disable
- C. ip audit attack signature (sig#) disable
- D. ip audit signature (sig#) disable
- E. None of the above

Answer: D

Explanation:

Use the ip audit signature (signature number) disable command to stop the IOS Firewall from scanning traffic for that signature attack.

QUESTION 104:

Kathy the security administrator is working on the IOS Firewall IDS feature. She needs to select the command used to configure the IOS Firewall IDS to globally disable a specific signature.

- A. ip audit signature sig-id global
- B. ip audit signature sig-id disable
- C. ip audit disable sig-id
- D. ip audit disable signature sig-id

Answer: B

Explanation

To attach a policy to a signature, use the ip audit signature command in global configuration mode. To remove the policy, use the no form of this command. If the policy disabled a signature, then the no form of this command reenables the signature. If the policy attached an access list to the signature, the no form of this command removes the access list.

ipaudit signature signature-id {disable | list acl-list}

noip audit signature signature-id

Syntax Description:

signature-id - Unique integer specifying a signature as defined in the NetRanger Network Security Database.

Disable - Disables the ACL associated with the signature.

List - Specifies an ACL to associate with the signature.

acl-list - Unique integer specifying a configured ACL on the router. Use with the list keyword.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps5207/products_command_reference_chapter09186a00801a

QUESTION 105:

You need to configure a Certkiller router to support IPS features. What is the purpose of the "ip ips sdf builtin" command?

- A. to load IPS on a router using the built-in signatures
- B. to load IP on a router using the attack-drop signatures
- C. to unload IPS built-in signatures
- D. to delete the IPS built-in signatures
- E. to load IPS on a router using the built-in micro-engine
- F. to disable IPS on a router using the built-in micro-engine

Answer: A

Explanation:

Normally, when an IPS router boots up, the built-in signature files are loaded. To instruct the router not to load the built-in signatures if it cannot find the specified signature definition files (SDFs), use the "no ip ips sdf builtin" command in global configuration mode. To instruct the router to use the pre-built signature files upon startup, use the "ip ips sdf builtin" command.

Note:

If the no ip ips sdf builtin command is issued and the router running Intrusion Prevention System (IPS) fails to load the SDF, you will receive an error message stating that IPS is completely disabled.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps5207/products_command_reference_chapter09186a008041

QUESTION 106:

John is the administrator at Certkiller Inc. and his assignment today is to find the two types of signature implementations that the IOS Firewall IDS can detect. Which two are correct? (Choose two)

- A. Atomic
- B. Compound
- C. Dynamic
- D. Regenerative
- E. Cyclical
- F. Complex

Answer: A, B

Explanation:

Cisco IOS Firewall IDS Signature List

The following is a complete list of Cisco IOS Firewall IDS signatures. A signature detects patterns of misuse in network traffic. In Cisco IOS Firewall IDS, signatures are categorized into four types:

1. Info Atomic
2. Info Compound
3. Attack Atomic
4. Attack Compound

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1835/products_configuration_guide_chapter09186a00800c

QUESTION 107:

James the administrator of Certkiller Inc. is working on the IDS for the network. He needs to know what kind of signatures trigger on a single packet. (Choose one)

- A. Regenerative
- B. Cyclical
- C. Dynamic
- D. Atomic
- E. Compound

Answer: D

The signature structure indicates whether the signature implementation is either content or composite. Atomic signatures occur in a single packet, whereas composite signatures can be spread across multiple packets.

Reference: Cisco Secure Intrusion Detection System (Cisco Press) page 192

QUESTION 108:

What type of IDS attack is spread out over multiple packets?

- A. Atomic
- B. Arbitrary
- C. Aggregate

- D. Compound
- E. None of the above

Answer: D

Explanation:

When an IDS signature attack uses multiple packets, it's called a compound attack. For the IOS Firewall to detect this type of attack, it must keep suspicious packets in memory to follow up on later packets of the session to see if it is an actual attack.

QUESTION 109:

You wish to disable the signature with ID 1000 on your router. Choose the correct command to disable signature 1000 in the SDF file on this router.

- A. 1000 disable
- B. no ip ips signature 1000
- C. no ip ips dignature 1000 enable
- D. ip ips signature 1000 disable
- E. ip signature 1000 disable
- F. signature 1000 disable

Answer: D

Explanation:

To instruct the router to scan for a given signature but not take any action if the signature is detected, use the ip ips signature command in global configuration mode.

```
ip ips signature signature-id [sub-signature-id] disable [listacl-list]
```

You may want to disable a signature (or set of signatures) if your deployment scenario deems the signatures unnecessary. The following example shows how to instruct the router not to report on signature 1000, if detected:

```
CK1 (config)#ip ips signature 1000 disable
```

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps5207/products_command_reference_chapter09186a00801a

QUESTION 110:

Choose the correct command that will load the SDF into a new Certkiller router and merge the new signatures with those that are already loaded in this router.

- A. copy flash ips-sdf
- B. copy url ips-sdf
- C. copy ips-sdf url
- D. write flash ips-sdf
- E. write ips-sdf url

F. write url ips-sdf

Answer: B

Explanation:

Issue the copy url ips-sdf command to load the SDF in the router from the location specified via the url argument. When the new SDF is loaded, it is merged with the SDF that is already loaded in the router, unless the /erase keyword is issued, which overwrites the current SDF with the new SDF.

CiscoIOS Intrusion Prevention System (IPS) will attempt to retrieve the SDF from each specified location in the order in which they were configured in the startup configuration. If Cisco IOS IPS cannot retrieve the signatures from any of the specified locations, the built-in signatures will be used.

If the no ip ips sdf built-in command is used, Cisco IOS IPS will fail to load. IPS will then rely on the configuration of the ip ips fail command to either fail open or fail closed.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps5207/products_command_reference_chapter09186a00801a

QUESTION 111:

The SDF uses which type of file format, with a definition of each signature along with relevant configurable actions?

- A. ASCII
- B. HTML
- C. JPEG
- D. Word
- E. Text
- F. XML
- G. None of the above

Answer: F

Explanation:

Signature Definition File (SDF):

The SDF is integral to Cisco IOS Software IPS. The SDF is an Extensible Markup Language (XML) file with a definition of each signature along with relevant configurable actions. Cisco IOS Software IPS reads in the SDF, parses the XML, and populates its internal tables with the information necessary to detect each signature. The SDF contains the signature definition and configuration. Actions such as alarm, drop, or reset can be selected for individual signatures within the SDF. The SDF can be modified so the router will only detect specific signatures; as a result, it can contain all or a subset of the signatures supported in Cisco IOS Software IPS. The user specifies the location of the SDF. The SDF can reside on the local flash file system (recommended) or on a remote server.

Reference:

http://www.cisco.com/en/US/products/ps6634/products_white_paper0900aecd80327257.shtml

QUESTION 112:

Router CK1 is being configured for IPSec. After configuring multiple transform sets, where do you specify the transform sets?

- A. ACL
- B. ISAKMP policy
- C. Router interface
- D. Crypto map entry

Answer: D

Explanation:

The "crypto map set transform-set" command is used to specify which transform sets can be used with the crypto map entry. List multiple transform sets in order of priority, with the highest-priority transform set first.

Reference: Cisco Secure PIX Firewall (Cisco Press) page 217

QUESTION 113:

Two Certkiller hosts need to securely pass data between them. Which ESP mode is used to provide end-to-end protection of message payload between two hosts?

- A. Transport mode
- B. Encrypted mode
- C. ESP mode
- D. Tunnel mode
- E. None of the above

Answer: A

Explanation:

With ESP, there are two modes of operation: transport mode is used to encrypt normal connections between two hosts; tunnel mode encapsulates the original package in a new header. Tunnel mode is to be used when the destination is a VPN gateway.

QUESTION 114:

DRAG DROP

You have entered configuration mode on a new Certkiller VPN router in order to create an ISAKMP policy using pre-shared keys, 3DES encryption, and DH Group 2. Click and drag the five necessary commands to the ordered steps below:

642-503

Crypto ike enable	Step 1
Crypto isakmp enable	Step 2
Crypto isakmp policy	Step 3
Crypto isakmp policy 1	Step 4
Pre-share	Step 5
Authentication pre-share	
3DES	
Encryption 3des	
Group 2	

Answer:

Crypto ike enable	Crypto isakmp enable
	Crypto isakmp policy 1
Crypto isakmp policy	Authentication pre-share
	Encryption 3des
Pre-share	Group 2
3DES	

QUESTION 115:

Crypto access lists have been configured on a Certkiller IPSec router. What are two functions that crypto ACLs perform? (Choose two)

- A. Bypasses outbound traffic that should be protected by IPSec
- B. Select inbound traffic that should be protected by IPSec
- C. Selects outbound traffic that should be protected by IPSec
- D. Sends outbound traffic that should not be protected by IPSec as clear text
- E. Discards outbound traffic that should not be protected by IPSec
- F. Discards outbound traffic that requires protection by IPSec

Answer: C, D

Explanation:

Crypto access lists are used to define which IP traffic will be protected by crypto and which traffic will not be protected by crypto. For example, access lists can be created to protect all IP traffic between Subnet A and Subnet Y or between Host A and Host B. (These access lists are similar to access lists used with the access-group command. With

the access-group command, the access-list determines which traffic to forward or block at an interface.)

The access lists themselves are not specific to IPSec. It is the crypto map entry referencing the specific access list that defines whether IPSec processing is applied to the traffic matching a permit in the access list. For traffic not matching, the packets are to be process normally and forwarded as clear text.

Crypto access lists associated with IPSec crypto map entries have four primary functions:

1. Select outbound traffic to be protected by IPSec (permit = protect).
2. Indicate the data flow to be protected by the new security associations (specified by a single permit entry) when initiating negotiations for IPSec security associations.
3. Process inbound traffic to filter out and discard traffic that should have been protected by IPSec.
4. Determine whether or not to accept requests for IPSec security associations on behalf of the requested data flows when processing IKE negotiation from the peer. (Negotiation is only done for ipsec-isakmp crypto map entries.) In order for the peer's request to be accepted during negotiation, the peer must specify a data flow that is "permitted" by a crypto access list associated with an ipsec-isakmp crypto map command entry.

Reference:

http://www.cisco.com/en/US/products/sw/secursw/ps2120/products_user_guide_chapter09186a0080089921.htm

QUESTION 116:

A co-worker at Certkiller wants to know which type of key exchange mechanism is Diffie-Hellman. What is the correct answer?

- A. Private key exchange
- B. RSA keying
- C. Public key exchange
- D. AES key exchange
- E. All of the above.

Answer: C

Explanation:

Diffie-Hellman is used to securely exchange public keys so that shared secret keys can be securely generated for use as DES keys.

Reference: Managing Cisco Network Security (Cisco Press) page 467

QUESTION 117:

John the security administrator is configuring a Cisco router for IPSec using pre-shared keys, why should he configure a crypto map with two peers specified for redundancy?

- A. The second peer becomes the primary peer.

- B. The second peer monitors activity of the first peer.
- C. If the first peer cannot be contacted, the second peer is used.
- D. There are not circumstances in which you should do this.

Answer: C

Explanation:

You can define multiple peers by using crypto maps to allow for redundancy. If one peer fails, there will still be a protected path. The peer that packets are actually sent to is determined by the last peer that the PIX Firewall heard from (received either traffic or a negotiation request from) for a given data flow. If the attempt fails with the first peer, IKE tries the next peer on the crypto map list.

QUESTION 118:

You are configuring IPsec on one of the Certkiller routers. Choose the correct command to allow IKE to establish the IPsec security associations on this router.

- A. crypto map 10 isakmp
- B. crypto map 10 manual
- C. crypto map MYMAP ipsec-isakmp
- D. crypto map MYMAP ipsec-manual
- E. crypto map MYMAP 10 ipsec-isakmp
- F. crypto map MYMAP 10 ipsec-manual

Answer: E

Explanation:

Creating Crypto Map Entries that Use IKE to Establish Security Associations:

When IKE is used to establish security associations, the IPsec peers can negotiate the settings they will use for the new security associations. This means that you can specify lists (such as lists of acceptable transforms) within the crypto map entry.

To create crypto map entries that will use IKE to establish the security associations, use the following command in global configuration mode:

Step	Command	Purpose
1	crypto map <i>map-name seq-num</i> ipsec-isakmp	Names the crypto map entry to create (or modify). This command puts you into the crypto map configuration mode.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1831/products_configuration_guide_chapter09186a00803

4

QUESTION 119:

The following output was seen from the Certkiller router named R2:

R2#sh crypto ipsec sa

```
interface: FastEthernet0/1
  Crypto map tag: MYMAP, local addr 172.30.2.2

protected vrf: (none)
local ident (addr/mask/prot/port): (172.30.2.2/255.255.255.255/0/0)
remote ident (addr/mask/prot/port): (172.30.7.2/255.255.255.255/0/0)
current_peer 172.30.7.2 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 4, #pkts encrypt: 4, #pkts digest: 4
#pkts decaps: 4, #pkts decrypt: 4, #pkts verify: 4
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 1, #recv errors 0

local crypto endpt.: 172.30.2.2, remote crypto endpt.: 172.30.7.2
path mtu 1500, ip mtu 1500
current outbound spi: 0x5FAA1A55(1604983381)

inbound esp sas:
  spi: 0x2831CBC6(674352070)
  transform: esp-des,
  in use settings = (Tunnel, )
  conn id: 2001, flow_id 1, crypto map: MYMAP
  sa timing: remaining key lifetime (k/sec): (4511705/3537)
  IV size: 8 bytes
  replay detection support: N
  Status: ACTIVE

inbound ah sas:

inbound pcp sas:

outbound esp sas:
  spi: 0x5FAA1A55(1604983381)
  transform: esp-des,
  in use settings = (Tunnel, )
  conn id: 2002, flow_id 2, crypto map: MYMAP
  sa timing: remaining key lifetime (k/sec): (4511705/3524)
  IV size: 8 bytes
  replay detection support: N
  Status: ACTIVE
```

Given the output of the show crypto ipsec sa command shown above, which encryption algorithm is being used?

- A. PCP
- B. ESP
- C. DES
- D. 3DES
- E. AH

F. HMAC

Answer: C

Explanation:

With any IPSec communication process, there are really two separate uni-directional tunnels being created. One is used for inbound traffic, and the other is used for outbound communications. As can be seen from the output shown above, the transform set for each is specified as ESP-DES, meaning that the ESP is used (as opposed to the alternative AH), and DES is being used as the encryption algorithm.

QUESTION 120:

You are configuring the IPSEC timers on a Certkiller router. Which of the following commands correctly sets the IPSEC SA lifetime value to 30 minutes?

- A. `crypto ipsec sa lifetime 30`
- B. `crypto ipsec security-association lifetime 1800`
- C. `crypto ipsec sa lifetime 1800`
- D. `crypto ipsec security-association lifetime 30`

Answer: B

Explanation:

The IPSEC SA lifetime value can be configured between 120 and 86,400 seconds with the command: `crypto ipsec security-association lifetime (seconds)`. You can also set the IPSEC SA lifetime value in kilobytes transmitted with the `crypto ipsec security-association lifetime kilobytes (kilobytes)` command. Whenever either value (seconds elapsed or kilobytes transmitted) is reached, the Security Associations will need to be renegotiated. These commands can be entered in global configuration mode, thus applying them to all SA's, or can be configured in crypto map configuration mode. Lifetime values entered in crypto map configuration will override the global configuration values.

QUESTION 121:

You need to configure a Certkiller router for IPSEC. Which of the following correctly configures authentication and encryption for an IPSEC transform set?

- A. `crypto ipsec transform-set secure ah-hmac-md5 esp-des`
- B. `crypto ipsec transform-set secure ah-md5 esp-3des`
- C. `crypto ipsec transform-set secure esp-sha-hmac esp-3des`
- D. `crypto ipsec transform-set secure ah-md5 esp-des-hmac`

Answer: C

Explanation:

This transform set uses esp-3des for encryption, and uses esp-sha-hmac for authentication. The transform set in answer D is close, but the authentication transform would need to read like this: ah-md5-hmac.

QUESTION 122:

You want to configure a Certkiller router for IPSec using default values. Which of the following is NOT an IOS Firewall default IKE policy parameter?

- A. MD5
- B. DH group 1
- C. DES
- D. Lifetime 86,400 seconds
- E. RSA-Signatures

Answer: A

Explanation:

Answers A through E are the default IOS Firewall router IKE policy values, except for answer A, MD5. (The default IKE hash algorithm used is SHA-1). Although MD5 can be configured, the default is SHA-1.

QUESTION 123:

You need to configure a Cisco router for IPSec. Which of the following Cisco IOS router commands will properly configure pre-shared keys for IKE authentication?

- A. Router(config-crypto)#authentication pre-share
- B. Router(config-policy)#authentication pre-share
- C. Router(config-isakmp)#authentication pre-share
- D. Router(config-ike)#authentication pre-share

Answer: C

Explanation:

Configure IKE policy parameters in isakmp configuration mode (Router(config-isakmp)#).

The initial detailed steps are as follows:

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: Router> enable	Enables privileged EXEC mode. • Enter your password if prompted.
Step 2	configure terminal Example: Router# configure terminal	Enters global configuration mode.
Step 3	crypto isakmp policy Example: Router(config)# crypto isakmp policy 1	Defines an Internet Key Exchange (IKE) policy and enables ISAKMP policy configuration mode.
Step 4	encryption Example: Router(config-isakmp)# encryption 3des	Specifies the encryption algorithm within an IKE policy.
Step 5	hash Example: Router(config-isakmp)# hash md5	Specifies the hash algorithm within an IKE policy.
Step 6	authentication Example: Router(config-isakmp)# authentication pre-share	Specifies the authentication method within an IKE policy.
Step 7	exit Example: Router(config-isakmp)# exit	Exits ISAKMP policy configuration mode and enables global configuration mode.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps5012/products_feature_guide_chapter09186a008032a106.html

QUESTION 124:

You are configuring a Certkiller router for IPSec. What type of crypto map would you need to create if you are using IKE for IPSEC?

- A. crypto map map1 100 ipsec-manual
- B. crypto map map1 100 ike-dynamic
- C. crypto map map1 100 ipsec-isakmp
- D. crypto map map1 100 isakmp-key
- E. crypto map map1 100 dynamic

F. None of the above

Answer: C

Explanation:

When creating a crypto map, specify that the map will use IKE with the ipsec-isakmp keyword. If you are not using IKE, and are instead using manual keys, enter the ipsec-manual crypto map keyword.

QUESTION 125:

You want to configure a Certkiller router for IPSec using default values. What is the IOS Firewall IPSEC SA default lifetime value (in seconds)?

- A. 50,400
- B. 3,600
- C. 21,600
- D. 86,400

Answer: B

Explanation:

The default IPSEC SA lifetime value is set to 3600 seconds (1 hour). Do not confuse this IPSEC SA lifetime value with the ISAKMP (IKE) SA lifetime value which is set to 86,400 seconds (1 day) by default.

QUESTION 126:

The security administrator at Certkiller wants to use the most secure approach for using pre-shared keys between peers. Which one of these answers is the most secure?

- A. Specify the same key to share with multiple remote peers.
- B. Specify different keys to share between different pairs of peers.
- C. Specify different keys to share with multiple remote peers.
- D. Specify the same key to share between different pairs of peers.
- E. None of the above

Answer: B

Explanation:

Specify the shared keys at each peer. A given pre-shared key is shared between two peers. At a given peer you could specify the same key to share with multiple peers; however, a more secure approach is to specify different keys to share between different pairs of peers.

Reference:

http://www.cisco.com/en/US/products/sw/secursw/ps2120/products_user_guide_chapter09186a0080106f69.htm

QUESTION 127:

Jason is the security administrator at Certkiller Inc. and his assignment today is to find out in crypto map configuration mode, which command lets you manually specify the IPSec session keys with a crypto map entry?

- A. set crypto map
- B. set ipsec-manual
- C. no set security-association
- D. set security-association

Answer: D

Explanation:

To specify that separate IP Security security associations should be requested for each source/destination host pair, use the set security-association level per-host crypto map configuration command. To specify that one security association should be requested for each crypto map access list permit entry, use the no form of this command.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1835/products_command_summary_chapter09186a008008

QUESTION 128:

Regarding IPSec and Certificate Authorities (CA), which of the following choices define the standard certificate format?

- A. CEP
- B. CRLv2
- C. ISAKMP
- D. X.509v3
- E. None of the above

Answer: D

Explanation:

The X.509 standard specifies that digital certificates contain standardized information. A CA (Certificate Authority) vouches for the authenticity of their public keys. A digital signature which meets ITU (International Telecommunications Union) Telecommunication Standardization (ITU-T) PKIX X.509 version 3 [RFC 2459] standard is generated based on

1. detailed information about the key holder

2. an expiration date, after which the certificate is expired
3. (with v3), a Compromised Key List (CKL)

Reference:

<http://www.microsoft.com/technet/prodtechnol/exchange/guides/E2k3MsgSecGuide/b26b91d9-d569-4d1f-914fLeading>
the way in IT testing and certification tools, www.Certkiller.com

QUESTION 129:

A Certkiller IPsec device is being configured for CA support. Choose the correct command to generate two RSA key pairs for use with certificate authority.

- A. key generate rsa general-keys
- B. key generate rsa usage-keys
- C. crypto key generate rsa general-keys
- D. crypto key generate rsa usage-keys
- E. enable crypto key generate rsa general-keys
- F. enable crypto key generate rsa usage-keys

Answer: D

Explanation:

Special-Usage Keys:

If you generate special-usage keys, two pairs of RSA keys will be generated. One pair will be used with any Internet Key Exchange (IKE) policy that specifies RSA signatures as the authentication method, and the other pair used with any IKE policy that specifies RSA-encrypted nonces as the authentication method. (You configure RSA signatures or RSA-encrypted nonces in your IKE policies as described in the Cisco IOS Security Configuration Guide.)

A certification authority (CA) is used only with IKE policies specifying RSA signatures, not with IKE policies specifying RSA-encrypted nonces. (However, you could specify more than one IKE policy and have RSA signatures specified in one policy and RSA-encrypted nonces in another policy.)

If you plan to have both types of RSA authentication methods in your IKE policies, you might prefer to generate special-usage keys. With special-usage keys, each key is not unnecessarily exposed. (Without special-usage keys, one key is used for both purposes, increasing that key's exposure.)

To generate special-usage RSA keys, use the "crypto key generate rsa usage-keys" command.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1839/products_feature_guide09186a0080087cac.html

QUESTION 130:

You are configuring a new Certkiller router for CA support. Which of the following router commands correctly sets the location (URL) of a CA server into the router

configuration?

- A. Router (crypto-set)#enrollment mode (URL)
- B. Router (crypto-ca)#enrollment mode (URL)
- C. Router (ca-scep)#enrollment url (URL)
- D. Router (ca-identity)#enrollment url (URL)

Answer: D

Explanation:

Specify the location of the CA server with the ca-identity configuration mode command enrollment url (URL).

To configure the PKI, use the following commands beginning in privileged EXEC mode (first 7 steps only shown):

	Command	Purpose
Step 1	Router# configure terminal	Enters global configuration mode.
Step 2	Router(config)# no crypto ca id name	Clears the old certificate if one exists.
Step 3	Router(config)# crypto key zeroize rsa	Clears the existing RSA key.
Step 4	Router(config)# hostname router-name	Configures the router hostname if this has not been done already.
Step 5	Router(config)# ip domain-name domain-name	Configures the router's IP domain name.
Step 6	Router(config)# crypto ca identity name	Enters CA-identity configuration mode and declares a Certification Authority (CA) name. For example, the CA name could be fieldlabs.cisco.com.
Step 7	Router(ca-identity)# enrollment url url	Uses a nonstandard <code>cgi-bin</code> script location URL.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1831/products_configuration_guide_chapter09186a00800

c

QUESTION 131:

The security administrator at Certkiller Inc. must choose three major tasks that must be completed in order to support CA for Cisco routers in a site-to-site configuration. What are these three steps? (Choose three)

- A. Configure an authentication proxy.
- B. Configure a CA server.
- C. Configure IKE.
- D. Test and verify IPsec.
- E. Test and verify the RADIUS server.
- F. Configure CA support.

Answer: C, D, F

Explanation:

The tasks for configuring IPsec operation for CA support is as follows:

Task 1: Prepare for IPsec

Task 2: Configure CA support

Task 3: Configure IKE for IPsec

Task 4: Configure IPsec

Task 5: Verify VPN configuration - Verify IPsec

Reference: Managing Cisco Network Security (Cisco Press) page 646

QUESTION 132:

What is the bit length of the Diffie-Hellman group 1 algorithm?

- A. 768 bits
- B. 512 bytes
- C. 512 bits
- D. 768 bytes
- E. 1024 bits
- F. 2048 bits
- G. None of the above

Answer: A

Explanation:

The Diffie-Hellman protocol uses complex mathematical algorithms to generate a secret key over an insecure link such as the Internet. Only the public keys are exchanged, the secret key that is generated is never sent over the link. Diffie-Hellman group 1 uses 768 bit keys.

QUESTION 133:

Which of the following commands can debug communications between an IOS router, and a CA server?

- A. debug crypto dss exchange
- B. debug crypto ca server
- C. debug crypto ca engine
- D. debug crypto pki messages

Answer: D

Explanation:

You can monitor the communication between a router and a Certificate Authority (CA) server with the debug crypto pki messages command.

QUESTION 134:

The newly appointed Certkiller trainee technician wants to know of which cryptographic key system RSA is an example of. What would your reply be?

- A. symmetrical
- B. asymmetrical
- C. Diffie-Hellman
- D. DES

Answer: B

There are two types of cryptographic keys; public keys -- sometimes called asymmetric key -- and symmetric keys. RSA and Diffie-Hellman are common public key algorithms and RC4, DES and IDEA common symmetric key algorithms. You cannot directly compare public key lengths (for example RSA keys) with symmetric key lengths (DES, RC4); this is an important point which confuses many people.

QUESTION 135:

The security team at Certkiller Inc., is looking for the command that lets you view any configured CA certificates?

- A. crypto key generate rsa
- B. show crypto key mypubkey rsa
- C. show crypto key pubkey-chain rsa
- D. show crypto ca certificates

Answer: D

To view information about your certificate, the CA's certificate, and any RA certificates, use the "show crypto ca certificates" EXEC command.

QUESTION 136:

The Certkiller trainee technician wants to know which error message indicates that ISAKMP peers failed protection suit negotiation for ISAKMP. What will your reply be?

- A. %Crypto-6-IKMP_SA_AUTH Can accept Quick Mode exchange form % 15 if SA is authenticated
- B. %Crypto-6-IKMP_SA_OFFERED Remote peer% respond attribute [chars] offered
- C. %Crypto-6-IKMP_SA_NOT_OFFERED Remote peer% respond attribute [chars] not offered
- D. %Crypto-6-IKMP_SA_NO_AUTH Remote peer% respond attribute [chars] not offered

Answer: C

Explanation:

Error Message:

%CRYPTO-6-IKMP_SA_NOT_OFFERED : Remote peer [IP_address] responded with attribute [chars] not offered or changed

ExplanationIKE peers negotiate policy by having the initiator offer a list of possible protection suites. The responder has returned a type of protection suite that the initiator did not offer.

Recommended ActionContact the remote peer.

Reference:

<http://www.cisco.com/univercd/cc/td/doc/product/software/ios122/122sup/122sems/semsvoll1/emfcpad.htm>

QUESTION 137:

Jason the security manager at Certkiller Inc. is working on the PIX firewall. He needs to figure out which two types of commands are used for testing and verifying IPsec and ISAKMP? (Choose two)

- A. clear
- B. show
- C. interface
- D. crypto map
- E. crypto isakmp policy
- F. debug

Answer: B, F

Explanation:

Testing and verifying the overall IPsec configuration:

The final step in configuring IPsec for pre-shared keys is to verify that all the IKE and

IPSec values were configured correctly and to test it to ensure that it works properly. The PIX Firewall contains a number of show, clear, and debug commands that are useful for testing and verifying IKE and IPSec, which are summarized in this section.

Reference: Managing Cisco Network Security (Cisco Press) page 221

QUESTION 138:

What IOS router command is entered to view all current IKE SA's?

- A. show ipsec
- B. show crypto isakmp sa
- C. show isakmp
- D. show crypto ipsec sa
- E. show ipsec sa
- F. show isakmp sa

Answer: B

Explanation:

View the status of current IKE Security Associations on a router with the show crypto isakmp sa command. (ISAKMP is the same process as IKE)

QUESTION 139:

Regarding IPSec operation, what are the protocol numbers used for ESP and AH?

- A. 84, 85
- B. 69, 70
- C. 50, 51
- D. 96, 97

Answer: C

Explanation:

The two IPSEC protocols ESP (encryption and authentication), and AH (authentication) are protocol numbers 50, and 51, respectively.

QUESTION 140:

Kathy is looking for the command that deletes all of the routers RSA keys. Which command is correct?

- A. crypto key zeroize rsa
- B. crypto key remove rsa
- C. crypto key delete rsa
- D. crypto key remove rsa all

Answer: A

Explanation:

To delete all of your router's RSA keys, use the crypto key zeroize rsa global configuration command.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1828/products_command_summary_chapter09186a00800e

QUESTION 141:

John the security Administrator at Certkiller Inc. is working on IPSec. He quizzes Kathy about AH. He asks her which three statements about AH are true. (Choose three)

- A. AH encrypts the payload for data confidentiality.
- B. AH provides connectionless integrity for the IP datagrams.
- C. AH encapsulates the data.
- D. AH provides protection against replay.
- E. AH uses symmetric secret algorithms.
- F. AH provides data origin authentication for the IP datagrams.

Answer: B, D, F

Explanation:

Authentication Header - A security protocol that provides authentication and optional replay-detection services. AH acts as a digital signature to ensure data in the IP packet has not been tampered with. AH does not provide data encryption and decryption services.

Reference: Managing Cisco Network Security (Cisco Press) page 525

QUESTION 142:

A Certkiller router is being configured for IPSec using ESP. Which of the following are true regarding ESP? (Choose three)

- A. ESP provides protection to the outer headers.
- B. ESP encapsulates the data.
- C. ESP uses symmetric secret key algorithms.
- D. ESP verifies the integrity of the ESP datagram.
- E. ESP uses asymmetric secret key algorithms.
- F. ESP encrypts the payload for data confidentiality.

Answer: B, C, F

Explanation:

ESP is a security protocol used to provide confidentiality (that is, encryption), data origin authentication, integrity, optional anti-replay service, and limited traffic flow confidentiality by defeating traffic flow analysis.

ESP provides confidentiality by performing encryption at the IP packet layer. It supports a variety of symmetric encryption algorithms.

Reference: Managing Cisco Network Security (Cisco Press) page 529

QUESTION 143:

John the security administrator at Certkiller Inc. is using Cisco Easy VPN and needs to know which of these statements are true about Cisco Easy VPN.

- A. All members of a user group must originate on the same model and type of Cisco VPN Client.
- B. Only VPN-enabled Cisco routers and PIX Firewalls may be used as Easy VPN servers.
- C. The maximum amount of Cisco VPN Clients supported by a VPN server is 50.
- D. Centrally managed IPSec policies are pushed to the Cisco VPN Clients by the VPN server.

Answer: D

Explanation:

The Easy VPN Server feature introduces server support for the Cisco VPN Client Release 3.x and later software clients and Cisco VPN hardware clients. The feature allows a remote end user to communicate using IP Security (IPSec) with any CiscoIOS Virtual Private Network (VPN) gateway. Centrally managed IPSec policies are "pushed" to the client by the server, minimizing configuration by the end user.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1839/products_feature_guide09186a0080087d1e.html#699

QUESTION 144:

The Certkiller security administrator is working on the Cisco Easy VPN. He needs to select the three types of IPSec encryption algorithms supported by Cisco Easy VPN. (Choose three)

- A. DES
- B. 3DES
- C. NULL
- D. ESP
- E. IPCOMP-LZS
- F. HMAC-MD5

Answer: A B C

Explanation:

Supported IPSec Protocol Options and Attributes

Encryption Algorithms (IPSec)

1. DES
2. 3DES
3. NULL

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1839/products_feature_guide09186a0080087d1e.html#105

QUESTION 145:

Which of the following represents the main components that the Cisco Easy VPN feature set consists of? (Choose two)

- A. Easy VPN CA
- B. Easy VPN RADIUS Server
- C. Easy VPN Access
- D. Easy VPN Server
- E. Easy VPN Remote
- F. Easy VPN TACACS+ Server

Answer: D, E

Cisco EzVPN consists of two components: Easy VPN Server, and Easy VPN Remote. The EzVPN Server is the Head-End VPN device and can push a configuration to the EzVPN Remote device.

QUESTION 146:

Two Certkiller devices are connected via the Cisco EZVPN service. Which Easy VPN feature enables two IPSec peers to determine if the other is still "alive"?

- A. Dead Peer Timeout
- B. No Pulse Timer
- C. Peer Death Monitor
- D. Dead Peer Detection
- E. Peer Heartbeat
- F. All of the above
- G. None of the above.

Answer: D

Explanation:

The IPSec Dead Peer Detection Periodic Message Option feature allows you to configure

your router to query the liveness of its Internet Key Exchange (IKE) peer at regular intervals. The benefit of this approach over the default approach (on-demand dead peer detection) is earlier detection of dead peers.

DPD and Cisco IOS keepalives function on the basis of the timer. If the timer is set for 10 seconds, the router will send a "hello" message every 10 seconds (unless, of course, the router receives a "hello" message from the peer). The benefit of IOS keepalives and periodic DPD is earlier detection of dead peers.

Reference:

http://www.cisco.com/en/US/products/ps6350/products_configuration_guide_chapter09186a0080455afd.html

QUESTION 147:

You are configuring a new Certkiller router with the EzVPN feature. What EzVPN feature allows a remote host to encrypt all data needing to go to the EzVPN Server, but sending all other traffic in clear text to its local ISP?

- A. Initial Contact
- B. DPD
- C. Split Tunneling
- D. Remote Administration
- E. None of the above

Answer: C

Explanation:

The Remote EzVPN client can be configured to use Split Tunneling which allows a connection to the EzVPN server, and a connection to the local ISP. This allows all traffic not destined to the EzVPN server to go to the ISP, unencrypted. If Split Tunneling is not used, all traffic will go to the EzVPN server encrypted, then rerouted out to the Internet to its final destination.

QUESTION 148:

You are configuring a new Certkiller router with the EzVPN feature. What is the EzVPN feature that allows a Remote host to re-establish a connection to a Server, if the Remote host is accidentally disconnected?

- A. Mode Configuration
- B. DPD
- C. Split Tunneling
- D. Initial Contact
- E. None of the above

Answer: D

Explanation:

Initial Contact is used by a host when first establishing a connection to the EzVPN Server, telling the Server to delete any previous SA's with the host. This is done because if a host is disconnected from the Server, and the Server is not aware of it, the host will not be able to reconnect with the Server unless the SA's are reset. Initial Contact makes sure the host can connect.

QUESTION 149:

You are configuring a new Certkiller router with the EzVPN feature. What are the two components of Cisco Easy VPN (EzVPN)?

- A. External
- B. Server
- C. Remote
- D. Master
- E. Slave
- F. Client

Answer: B, C

Explanation:

Cisco Easy VPN consists of two components: Cisco Easy VPN Remote and Cisco Easy VPN Server. The Cisco Easy VPN Remote feature allows Cisco IOS routers, Cisco PIX Security Appliances, Cisco VPN 3002 Hardware Clients and the Cisco VPN Client to receive security policies upon a VPN tunnel connection from a Cisco Easy VPN Server, minimizing configuration requirements at the remote location.

The Cisco Easy VPN Server allows Cisco IOS routers, Cisco PIX Security Appliances, and Cisco VPN 3000 Concentrators to act as VPN head-end devices in site-to-site or remote-access VPNs, where the remote office devices are using the Cisco Easy VPN Remote feature. This feature pushes security policies defined at the central site to the remote VPN device, helping to ensure that those connections have up-to-date policies in place before the connection is established. Additionally, a device enabled with the Cisco Easy VPN Server can terminate VPN tunnels initiated by mobile remote workers running the Cisco VPN Client software on PCs. This flexibility allows mobile and remote workers to access critical data and applications on their corporate intranet.

Reference: Cisco Self-Study CCSP SECUR page 363

QUESTION 150:

You are configuring a new Certkiller router with the EzVPN feature. What are the IPsec attributes that Cisco Easy VPN is incapable of supporting? (Choose all that apply)

- A. Manual keys
- B. PFS
- C. RSA digital signatures

- D. Tunnel mode
- E. DH 2
- F. Pre-shared keys

Answer: A, B

The following table lists the Non Supported IPSec Protocol Options and Attributes:

Options	Attributes
Authentication Types	Authentication with public key encryption Digital Signature Standard (DSS)
Diffie-Hellman Group	1
IPSec Protocol Identifier	IPSEC_AH
IPSec Protocol Mode	Transport mode
Miscellaneous	Manual keys Perfect Forward Secrecy (PFS)

QUESTION 151:

You are the administrator of Certkiller Inc. and your job today is to find out which Easy VPN feature enables two IPSec peers to determine if the other is still alive. What feature does this?

- A. Dead Peer Timeout
- B. Dead Peer Detection
- C. No Pulse Timer
- D. Peer Death Monitor
- E. Peer Heartbeat

Answer: B

Explanation:

The IPSec Dead Peer Detection Periodic Message Option feature allows you to configure your router to query the liveness of its Internet Key Exchange (IKE) peer at regular intervals. The benefit of this approach over the default approach (on-demand dead peer detection) is earlier detection of dead peers.

Reference:

http://www.cisco.com/en/US/products/ps6635/products_white_paper09186a00801ee19a.shtml

QUESTION 152:

You are configuring a new Certkiller router as an EzVPN client. Which of the following can act as a Cisco EzVPN Remote client? (Select all that apply)

- A. 1700 router
- B. 7200 router
- C. VPN Software Client
- D. 3002 VPN Hardware Client

Answer: A, C, D

Explanation:

The following devices can act as the Remote in a Cisco EzVPN: 800, 900, and 1700 series routers, PIX 501 firewall, the 3002 Hardware Client, and the VPN software client.

QUESTION 153:

The following command was issued on one of the Certkiller routers:

```
R7#sh crypto ipsec client ezvpn
Easy VPN Remote Phase: 2
Tunnel name : VPNGATE1
Inside interface list: FastEthernet0/0,
Outside interface: FastEthernet0/1
Current State: IPSEC_ACTIVE
Last Event: SOCKET_UP
Address: 10.0.2.39
Mask: 255.255.255.255
Default Domain: cisco.com
```

Given the output of the show crypto ipsec client ezvpn command shown above, what can you determine?

- A. The default domain is cisco
- B. The socket is up and ready for data.
- C. The remote router address is 10.0.2.39.
- D. The tunnel is up and SAs have been established.
- E. The tunnel is terminated at a remote router called VPNGATE1.
- F. All hosts connecting through this router will have the address of 10.0.2.39.

Answer: D

Explanation:

The following example shows a typical display from the show crypto ipsec client ezvpn command for an active Virtual Private Network (VPN) connection when the router is in client mode:

```
Router# show crypto ipsec client ezvpn
Tunnel name: hw1
Inside interface list: FastEthernet0/0, Serial1/0,
Outside interface: Serial0/0
Current State: IPSEC_ACTIVE
Last Event: SOCKET_UP
Address: 209.165.201.0
Mask: 255.255.255.224
DNS Primary: 209.165.201.1
DNS Secondary: 209.165.201.2
NBMS/WINS Primary: 209.165.201.3
NBMS/WINS Secondary: 209.165.201.4
Default Domain: cisco.com
```

The following example shows a typical display from the show crypto ipsec client ezvpn command for an inactive VPN connection:

```
Router# show crypto ipsec client ezvpn
Current State: IDLE
Last Event: REMOVE INTERFACE CFG
```

Router#

The table below describes significant fields shown by the show crypto ipsec client ezvpn command:

Field	Description
Current State	Displays whether the VPN tunnel connection is active or idle. Typically, when the tunnel is up, the current state is IPSEC ACTIVE.
Last Event	Displays the last event performed on the VPN tunnel. Typically, the last event before a tunnel is created is SOCKET UP.
Address	Displays the IP address used on the outside interface.
Mask	Displays the subnet mask used for the outside interface.
DNS Primary	Displays the primary domain name system (DNS) server provided by the Dynamic Host Configuration Protocol (DHCP) server.
DNS Secondary	Displays the secondary DNS server provided by the DHCP server.
Domain Name	Displays the domain name provided by the DHCP server.
NBMS/WINS Primary	Displays the primary NetBIOS Microsoft Windows Name Server provided by the DHCP server.
NBMS/WINS Secondary	Displays the secondary NetBIOS Microsoft Windows Name Server provided by the DHCP server.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps5207/products_command_reference_chapter09186a00801a

QUESTION 154:

You are configuring a new Certkiller router as an EZVPN server. What is the IOS version that first introduced EzVPN server?

- A. 12.2(6)T
- B. 12.3(1)T
- C. 12.2(5)T
- D. 12.2(8)T

Answer: D

Explanation:

Cisco 1700, 7100, and 7200 routers can act as an EzVPN server starting in IOS version 12.2(8)T.

QUESTION 155:

You are configuring a new Certkiller router with the EzVPN feature. What are the two Diffie-Hellman (DH) groups that the IOS EzVPN server supports?

- A. Group 2
- B. Group 1
- C. Group 3
- D. Group 4
- E. Group 5


Answer: A, E

Explanation:

The Cisco IOS EzVPN Server only supports Diffie-Hellman Groups 2 (1024 bit) and 5 (1536 bit). Group 1 (768 bit) is not supported.

QUESTION 156:

While working on a CSACS the following was seen:



Refer to the Cisco Secure ACS Administration Privileges setup screen in the exhibit above. Which button should be checked to give administrative privileges to everything?

- A. Add/Edit users in these groups
- B. Cancel
- C. Grant All
- D. Revoke All
- E. Setup of these groups
- F. Submit

Answer: C

Explanation:

To add a CiscoSecure ACS administrator account, follow these steps (first 4 steps only shown) below:

Step 1:

In the navigation bar, click Administration Control.

Step 2:

Click Add Administrator.

The Add Administrator page appears.

Step 3:

Complete the boxes in the Administrator Details table:

a.

In the Administrator Name box, type the login name (up to 32 characters) for the new CiscoSecure ACS administrator account.

b.

In the Password box, type the password (up to 32 characters) for the new CiscoSecure ACS administrator account.

c.

In the Confirm Password box, type the password a second time.

Step 4:

To select all privileges, including user group editing privileges for all user groups, click "Grant All".

Reference:

http://www.cisco.com/en/US/products/sw/secursw/ps2086/products_user_guide_chapter09186a0080205a43.htm

QUESTION 157:

A new Cisco ACS has been installed in the Certkiller network. Which three statements about Cisco Secure ACS are true? (Choose three.)

- A. NAS can access multiple Cisco Secure ACS for Windows servers.
- B. Cisco Secure ACS for Windows server can only log onto external server.
- C. The Cisco Secure ACS for Windows server supports only TACACS+.
- D. Database replication is supported by the Cisco Secure ACS for Windows servers.
- E. The service used for authentication and authorization on a Cisco Secure ACS for Windows server is called CSAdmin.
- F. The Cisco Secure ACS for Windows server uses the CSDBsynch service to manage the user and group accounts.

Answer: A, B, D

Explanation:

With ACS, the ability to determine if and where an authentication request is to be forwarded is defined in the distribution table in the Network Configuration window. Multiple CiscoSecureACSEs can be used throughout the network and, depending on a defined character string entered with the username (for example, mary@corporate.com, where @corporate.com is the defined character string), when the user dials in to the NAS and a match is found in the distribution table, the authentication request is then forwarded to a remote AAAserver to permit or deny access to the network.

The database replication and RDBMS synchronization features provided with CiscoSecureACS help automate the process of updating your CiscoSecureACS database and network configuration. Database replication allows you to replicate various parts of the configuration, including user and group information, from a CiscoSecureACS primary server to one or more CiscoSecureACS backup or client systems. Replication allows you to automate the creation of mirror CiscoSecureACSEs.

If your network is geographically dispersed, the remote logging feature helps you simplify the process of gathering the accounting logs generated on each CiscoSecureACS. Each CiscoSecureACS can be configured to point to a centralized CiscoSecureACS to be used as the logging server. The centralized CiscoSecureACS still has all the capabilities of a AAAserver but also becomes a central repository for all accounting logs that are sent.

Incorrect Answers:

C: Both TACACS and RADIUS are supported.

E: CSAuth is used for authorization and authentication on the Cisco Secure ACS, not CSAdmin.

F: CSDBSync is used to provide synchronization with an external RDBMS database, not for managing users and account info.

Reference:

http://www.cisco.com/en/US/products/sw/secursw/ps2086/products_user_guide_chapter09186a008007e350.htm

QUESTION 158:

You need to install CSACS 3.0 on a Certkiller server. How much hard disk space is required to install AAA CSACS 3.0 for Windows?

- A. 900mb
- B. 100mb
- C. 250mb
- D. 500mb
- E. None of the above

Answer: C

Explanation:

Installation of CSACS 3.0 on a Windows server will need at least 250Mb of disk space for installation, more if the user database will be stored on the machine.

QUESTION 159:

The security administrator at Certkiller Inc. needs to select three types of authentication supported by Cisco Secure ACS 3.0.1. What are the three methods? (Choose three)

- A. HMAC
- B. EAP-TLS
- C. DH-1
- D. AAA
- E. LEAP
- F. EAP-MD5

Answer: B, E, F

Explanation:

EAP-MD5, EAP-TLS-In addition to supporting LEAP, CiscoSecureACS supports EAP-MD5 and EAP-TLS authentication. EAP is an IETF RFC standard for carrying various authentication methods over any PPP connection. EAP-MD5 is a username/password method incorporating MD5 hashing for security. EAP-TLS is a method for authenticating both CiscoSecureACS and users with X.509 digital certificates. This method also provides dynamic session key negotiation.

Reference:

http://www.cisco.com/en/US/products/sw/secursw/ps2086/prod_release_note09186a00800ada4c.html

QUESTION 160:

A new Cisco ACS has been installed in the Certkiller network. Which of the following statements regarding Cisco Secure ACS are valid? (Choose three)

- A. The NAS is capable of accessing multiple Cisco Secure ACS for Windows server.
- B. The Cisco Secure ACS for Windows servers can log onto external servers.
- C. Database replication is supported by the Cisco secure ACS fro Windows servers.
- D. The service used for authentication and authorization on a Cisco.
- E. The Cisco Secure ACS for Windows server supports only TACACS+.
- F. The Cisco Secure ACS for Windows server uses the CSDBsynch service to manage the user and group accounts.

Answer: A, B, C

Explanation:

Cisco Secure ACS logs a variety of user and system activities. Depending on the log, and how you have configured Cisco Secure ACS, logs can be recorded in one of two formats: Comma-separated value (CSV) files-The CSV format records data in columns separated by commas. This format is easily imported into a variety of third-party applications, such as Microsoft Excel or Microsoft Access. After data from a CSV file is imported into such applications, you can prepare charts or perform queries, such as determining how many hours a user was logged in to the network during a given period. For information about how to use a CSV file in a third-party application such as Microsoft Excel, please see the documentation supplied by the third-party vendor. You can access the CSV files either on the Cisco Secure ACS server hard drive or by downloading the CSV file from the HTML interface. For more information about downloading the CSV file from the HTML interface, see the "Viewing a CSV Report" section.

ODBC-compliant database tables-ODBC logging enables you to configure Cisco Secure ACS to log directly in an ODBC-compliant relational database, where it is stored in tables, one table per log. After the data is exported to the relational database, you can use the data however you need. For more information about querying the data in your relational database, refer to the documentation supplied by the relational database vendor.

QUESTION 161:

AAA needs to be configured on one of the Certkiller routers. Which of the following router commands enables the AAA process?

- A. aaa new-model
- B. aaa setup-dbase
- C. aaa config-login
- D. aaa server-sync
- E. None of the above

Answer: A

Explanation:

Enable AAA by using the "aaa new-model" global configuration command.

AAA is an architectural framework for configuring a set of three independent security functions in a consistent manner. AAA provides a modular way of performing the following services:

Authentication-Provides the method of identifying users, including login and password dialog, challenge and response, messaging support, and, depending on the security protocol you select, encryption.

Authorization-Provides the method for remote access control, including one-time authorization or authorization for each service, per-user account list and profile, user group support, and support of IP, IPX, ARA, and Telnet.

Accounting-Provides the method for collecting and sending security server information used for billing, auditing, and reporting, such as user identities, start and stop times, executed commands (such as PPP), number of packets, and number of bytes.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1835/products_configuration_guide_chapter09186a00800c

QUESTION 162:

One of the Certkiller routers is configured as shown below:

```
!
username cisco password 0 cisco
memory-size iomem 10
clock timezone EDT -5
no network-clock-participate slot 1
no network-clock-participate wic 0
no aaa new-model
ip subnet-zero

interface FastEthernet0/0
ip address 10.0.2.2 255.255.255.0
duplex auto
speed auto
!
interface FastEthernet0/1
ip address 172.30.2.2 255.255.255.0
duplex auto
speed auto
!

line con 0
login local
line aux 0
line vty 0 4
password cisco
login
```

After reviewing the running configuration file shown above, what can you determine?

- A. No one will be able to login.
- B. No one will be able to console in.
- C. The wrong authentication method is applied to lines.
- D. Users will use the local database to log in to console.
- E. Users will use the password cisco to log in to console.
- F. Users will use the local database to log in to vty.

Answer: D

Explanation:

To establish a username-based authentication system, use the username command in global configuration mode. To enable password checking at login, use the login local command in line configuration mode. The login local could be used for console connections, as well as telnet connections into the router.

QUESTION 163:

The Certkiller security administrator was given the following configuration statement:

```
router(config)#aaa authentication login default tacacs+ none
```

After looking at the command, he knows two statements are true. Which two are

correct statements? (Choose two)

- A. TACACS is the default login method for all authentication.
- B. No authentication is required to login.
- C. IF TACACS process is unavailable, no access is permitted.
- D. RADIUS is the default login method for all authentication.
- E. If the RADIUS process is unavailable, no login is required.
- F. IF the TACACS process is unavailable, no login is required.

Answer: A, F

Explanation:

The command line in this question uses TACACS+ for authentication first. If a Cisco Secure ACS or TACACS is not available, use the NAS's local user database password. However, all other users can only use TACACS+: Finally, if both of these methods fail, then the "none" keyword specifies that no authentication is to be used, and to allow all users.

none - no authorization is performed.

Reference:

http://www.cisco.com/en/US/products/sw/secursw/ps4911/products_user_guide_chapter09186a008015c5c3.htm

QUESTION 164:

Which of the following configurations restricts telnet access to a Certkiller router by requiring the password "cisco"?

- A. line vty 0 4
login cisco
- B. line vty 0 4
set password cisco
login
- C. line vty 0 4
password cisco
login
- D. line vty 0 4
set login
set password cisco

Answer: C

Explanation:

To restrict telnet access to a Cisco router, you must configure the virtual terminal lines (VTY) that telnet uses. Require a login with the login line configuration command (enabled on vty lines by default). You must also set a password with the password

(password) line configuration command, or remote user telnet connections will be refused, informing them that a login is required, but no password is set.

QUESTION 165:

The TACACS server on your network has been issued the 10.1.1.4 IP address. Choose the correct global IOS command that will specify this TACACS server.

- A. host 10.1.1.4
- B. server 10.1.1.4
- C. tacacs-server host 10.1.1.4
- D. tacacs-server 10.1.1.4
- E. tacacs-host host 10.1.1.4
- F. server-tacacs host 10.1.1.4

Answer: C

Explanation:

The "tacacs-server host" command enables you to specify the names of the IP host or hosts maintaining a TACACS+ server. Because the TACACS+ software searches for the hosts in the order specified, this feature can be useful for setting up a list of preferred daemons.

The following example shows how to configure TACACS+ as the security protocol for PPP authentication:

```
aaanew-model
aaaauthenticationppptestgrouptacacs+local
tacacs-serverhost10.1.2.3
tacacs-serverkeygoaway
interfaceserial0
pppauthenticationchappapptest
```

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1835/products_configuration_guide_chapter09186a00800c

QUESTION 166:

You need to configure router CK1 to support AAA in the Certkiller network. Which configuration command on CK1 causes a start-accounting record for a Point-to-Point session to be sent to a TACACS+ server?

- A. aaa authentication ppp start tacacs+
- B. aaa authorization exec default tacacs+
- C. aaa authorization network default tacacs+
- D. aaa accounting network default stop-only tacacs+
- E. aaa accounting network default start-stop tacacs+

Answer: E

Explanation:

To enable AAA accounting of requested services for billing or security purposes when you use TACACS+, use the `aaaaccounting` global configuration command.

`aaa accounting {system | network | exec | command level} {start-stop | wait-start | stop-only} {tacacs+ | radius}`

Syntax Description

system	Performs accounting for all system-level events not associated with users, such as reloads.
network	Runs accounting for all network-related service requests, including SLIP, PPP, PPP NCPs, and ARAP.
exec	Runs accounting for EXEC session (user shells). This keyword might return user profile information such as autocommand information.
command	Runs accounting for all commands at the specified privilege level.
level	Specifies the command level to track for accounting. Valid entries are 0 through 15.
start-stop	Sends a start accounting notice at the beginning of a process and a stop accounting notice at the end of a process. The start accounting record is sent in the background. The requested user process begins regardless of whether or not the start accounting notice was received by the accounting server.
wait-start	As in start-stop , sends both a start and a stop accounting notice to the accounting server. However, if you use the wait-start keyword, the requested user service does not begin until the start accounting notice is acknowledged. A stop accounting notice is also sent.
stop-only	Sends a stop accounting notice at the end of the requested user process.
tacacs+	Enables the TACACS-style accounting.
radius	Enables the RADIUS-style authorization.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1824/products_command_reference_chapter09186a008008

QUESTION 167:

DRAG DROP

You need to configure your Certkiller router to enable AAA, start authentication and accounting using TACACS+ server 10.0.2.12 (with key: ciscosecure) using the default TACACS+ groups. Click and drag the correct commands to the ordered steps.

642-503

aaa new-model	Step 1
tacacs-server host 10.0.2.12	Step 2
tacacs server 10.0.2.12	Step 3
tacacs-server key ciscosecure	Step 4
aaa account connection default stop-start tacacs+	Step 5
aaa authentication user group tacacs+	
aaa authentication login default group tacacs+	
aaa account connect def start-stop group tacacs+	
aaa enable	

Answer:

aaa new-model
tacacs-server host 10.0.2.12
tacacs-server key ciscosecure
aaa account connection default stop-start tacacs+
aaa authentication login default group tacacs+

QUESTION 168:

Which of the following router commands will allow all of the Certkiller users to be authenticated, even if the TACACS+ server fails?

- A. aaa authentication list1 tacacs+ any
- B. aaa authentication list1 tacacs+ none
- C. aaa authentication list1 tacacs+ allow
- D. aaa authentication list1 tacacs+ disabled
- E. None of the above

Answer: B

Explanation:

The none keyword at the end of this aaa command allows the user to be authenticated by not requiring any form of authentication if the tacacs+ server is tried first, but did not respond.

QUESTION 169:

Which of the following represents a protocol that is commonly used to communicate AAA information between Cisco routers and AAA servers?

- A. TACACS+
- B. SSL
- C. Syslog

- D. SSH
- E. ARAP

Answer: A

Explanation:

Cisco uses the Terminal Access Controller Access Control System plus (TACACS+) protocol to communicate with remote AAA servers. TACACS is the Cisco proprietary method of communications, similar to the industry standard RADIUS method.

QUESTION 170:

You have been tasked to configure router CK1 to operate with the Certkiller RADIUS server. Choose the correct command to enable RADIUS authentication on the router.

- A. login default group radius
- B. aaa authentication login radius
- C. aaa authentication login group radius
- D. authentication login default group radius
- E. aaa authorization login default group radius
- F. aaa authentication login default group radius

Answer: F

Explanation:

Login Authentication

You can use the aaaauthentication login command to authenticate users who want exec access into the access server (tty, vty, console and aux).

Example 1: Exec Access using Radius then Local
aaa authentication login default group radius local

In the command above:

1. the named list is the default one (default).
2. there are two authentication methods (group radius and local).

All users are authenticated using the Radius server (the first method). If the Radius server doesn't respond, then the router's local database is used (the second method). For local authentication, define the username name and password:

```
username xxx password yyy
```

Because we are using the list default in the aaa authentication login command, login authentication is automatically applied for all login connections (such as tty, vty, console and aux).

Note: The server (Radius or TACACS+) will not reply to an aaa authentication request sent by the access server if there is no IP connectivity, if the access server is not correctly defined on the AAA server or the AAA server is not correctly defined on the access server.

Note: Using the example above, if we do not include the local keyword, we have:

aaa authentication login default group radius

Note:

If the AAA server does not reply to this authentication request, the authentication will fail (since the router does not have an alternate method to try).

Note: The group keyword provides a way to group existing server hosts. The feature allows the user to select a subset of the configured server hosts and use them for a particular service.

Reference:

http://www.cisco.com/en/US/tech/CK5_9/technologies_tech_note09186a0080093c81.shtml

QUESTION 171:

A Certkiller router needs to be configured to support RADIUS. Choose the correct command to set the RADIUS key to cisco for all RADIUS servers.

- A. router(config)# key cisco
- B. router(config)# server key cisco
- C. router(config)# radius-server cisco
- D. router(config)# radius key cisco
- E. router(config)# radius-server key cisco
- F. router(config-if)# radius-server key cisco

Answer: E

Explanation:

Timeout, retransmission, and encryption key values are applied globally to all RADIUS servers in the router configuration with three unique global commands: radius-server timeout, radius-server retransmit, and radius-server key.

If you have at least one RADIUS server that does not have a per-server key, use the radius-serverkey command in global configuration mode to set the authentication and encryption key for all RADIUS communications between the router and the RADIUS server.

Reference:

http://www.cisco.com/en/US/products/sw/iosswrel/ps1826/products_feature_guide09186a0080087cdc.html

QUESTION 172:

The following configuration was applied to a Certkiller router:

```
Certkiller Router(config)#aaa account network wait-start  
radius
```

According to the configuration statement shown above, which of the following statements are valid? *Choose all that apply)

- A. The accounting record are stored on a RADIUS server
- B. Start-accounting records for network service requests are sent to the local database.
- C. Stop-accounting record for network service requests are sent to the RADIUS server.

- D. The accounting records are stored on TACACS+ server.
- E. Stop-accounting record for network service requests are sent to TACACS+ server.
- F. The requested service cannot start until the acknowledgment has been received from the RADIUS server.

Answer: A, C, F

Explanation:

```
Router(config)#aaa accounting network wait-start radius
```

```
aaaaccounting {system | network | connection | exec | command level} {start-stop | wait-start | stop-only} tacacs+
```

* Use the aaaaccounting command to enable accounting and to create named method lists that define specific accounting methods on a per-line or per-interface basis.

* Network - Enables accounting for all network-related requests, including SLIP, PPP, PPP network control protocols, and ARAP

* wait-start - This keyword causes both a start and stop accounting record to be sent to the accounting server. However, the requested user service does not begin until the start accounting record is acknowledged. A stop accounting record is also sent.

QUESTION 173:


An AAA server has just been installed on your Cisco network. Which protocol is commonly used to communicate AAA information between Cisco routers and AAA servers?

- A. SSH
- B. ARAP
- C. TACACS+
- D. SSL
- E. Syslog

Answer: C

Explanation:

TACACS+ is an improved version of TACACS. TACACS+ forwards username and password information to a centralized security server. The diagram below shows a typical TACACS+ topology:



TACACS+ uses TCP as the communication protocol between the remote client and security server and it supports the AAA architecture.

QUESTION 174:

Part of the configuration file for router CK1 is shown below:

```
username cisco password 0 cisco
aaa new-model
aaa authentication login vty_in local
aaa authentication login con_in group tacacs+ local
aaa session-id common

interface FastEthernet0/0
 ip address 10.0.2.2 255.255.255.0
 duplex auto
 speed auto
!
interface FastEthernet0/1
 ip address 172.30.2.2 255.255.255.0
 duplex auto
 speed auto

accesslist 101 permit tcp any any eq 80

line con 0
 login authentication con_in
line aux 0
line vty 0 4
 password cisco
 login authentication vty_in
```

Refer to the exhibit above. The Certkiller administrator cannot telnet to the router. The administrator is not prompted for a username or password and cannot ping the router. After reviewing the output of a show running-config command, what do you determine is the problem?

- A. AAA is not enabled.
- B. Everything is configured correctly (the problem must be caused by something else).
- C. An access control list is blocking traffic.
- D. The wrong passwords are being used.
- E. The TACACS server must be unreachable.
- F. The wrong authentication method is applied to lines.

Answer: B

Explanation:

Based on the configuration shown above, users that telnet into the router are to be authenticated via the AAA line labeled "vty_in." This line says that the local user database should be used, so users that enter "cisco" as the username and "cisco" as the password will be granted access to the router. Therefore, everything is indeed configured

correctly, so there must be a different underlying problem. This is further reinforced by the fact that the router can also not be pinged.

Incorrect Answers:

A: This is enabled through the use of the "aaa new-model" command.

C: Although an access list is configured, it is not applied on any interface so it is not being used.

D: The problem in this case is that the users were not prompted for a username or a password.

E: The local database on the router is used for authentication, so this is not an issue.

F: The line configuration is correct.

QUESTION 175:

AAA is being configured on a new Certkiller router. Which of the following AAA security server protocols can the Cisco IOS Firewall support? (Select all that apply)

- A. MD5
- B. RSA Signatures
- C. TACACS+
- D. RADIUS
- E. CA
- F. IPSec

Answer: C, D

Explanation:

The IOS Firewall can communicate with an AAA server running either RADIUS or TACACS+. RADIUS is an industry standard method of AAA, while TACACS+ is a Cisco proprietary method.

QUESTION 176:

Which of the following are commands that can be entered on a Certkiller IOS Firewall router to debug communications with an AAA server? (Select all that apply)

- A. debug aaa all
- B. debug ip aaa
- C. debug aaa accounting
- D. debug tacacs
- E. debug interface tacacs
- F. None of the above

Answer: C, D

Explanation:

Use the "debug tacacs" command to just debug TACACS communication, or use a general command like "debug aaa accounting" for debugging TACACS and RADIUS.

QUESTION 177:

Which of the following router commands can you use to monitor AAA RADIUS?

- A. show radius errors
- B. show radius statistics
- C. show ip aaa
- D. show radius monitoring
- E. None of the above

Answer: B

Explanation:

Use the router command show radius statistics to view general RADIUS statistics for authentication and accounting.

QUESTION 178:

The Certkiller admin wants to connect to a router using SDM. Select the two protocols used to provide secure communications between SDM and the target router. (Select two)

- A. HTTPS
- B. RCP
- C. Telnet
- D. SSH
- E. HTTP
- F. AES

Answer: A, D

Explanation:

Cisco SDM communicates with routers for two purposes: to access the Cisco SDM application files for download to the PC and to read and write the router configuration and status. Cisco SDM uses HTTP(s) to download the application files to the PC. A combination of HTTP(s), Telnet/SSH is used to read and write the router configuration.

QUESTION 179:

Which of the following IOS commands should you use to enable local authentication for the HTTP interface.

- A. router# ip http authentication enable

- B. router# http authentication local
- C. router(config)# ip http authentication enable
- D. router(config)# ip http authentication local
- E. router(config)# ip http authentication enable local
- F. router(config)# ip http authentication local enable

Answer: D

Explanation:

The "ip http authentication" command enables you to specify a particular authentication method for HTTP server users. The HTTP server uses the enable password method to authenticate a user at privilege level 15. The "ip http authentication" command now lets you specify enable, local, TACACS, or authentication, authorization, and accounting (AAA) HTTP server user authentication.

Local Authentication with Cisco IOS Software Releases 11.3.3.T or later

!-- This is the part of the configuration related to local authentication.

```
!  
aaa new-model  
aaa authentication login default local  
aaa authorization exec default local  
username one privilege 15 password one  
username three password three  
username four privilege 7 password four  
ip http server  
ip http authentication local  
!
```

Reference:

http://www.cisco.com/en/US/tech/CK59/technologies_configuration_example09186a0080178a51.shtml

QUESTION 180:

You want to ensure that SDM has been successfully installed on router CK1 . Select the command below that is used to verify that SDM has been installed on a Cisco router.

- A. show manager
- B. show version
- C. show sdm
- D. show running-config
- E. show flash

Answer: E

Explanation:

Issue the "show flash" command on Cisco routers to ensure that SDM has been installed. The SDM files that will be visible from this command are the sdm.tar, sdm.shtml, and sdmconfig.cfg. All of these files are necessary to run the SDM on the router.

Reference: CCSP Self-Study Securing Cisco IOS Network (SECUR) Cisco Press, John F Roland Page 541

QUESTION 181:

You wish to ensure that you can use SDM on router CK1 . Which four files are required for basic HTTP connectivity to SDM? (Choose four)

- A. home.html
- B. home.tar
- C. home.cfg
- D. sdm.tar
- E. sdm.shtml
- F. sdmconfig-xxx.cfg

Answer: A, B, D, F

Explanation:

To verify that SDM files are present, issue the following CLI command:

Router# show flash:

If SDM software is present, you see output resembling the following:

System flash directory:

File Length Name/status

1 5148536 c831-k9o3y6-mz.122-13.ZH1.bin

2 14617 sdm.shtml

3 669 sdmconfig-83x.cfg

4 2290688 sdm.tar

5 14617 sdm.shtml.hide

6 1446 home.html

7 214016 home.tar

8 1446 home.html.hide

[7686035 bytes used, 17434224 available, 24903680 total]

24576K bytes of processor board System flash (Read/Write)

As can be seen by the output above, the home.html, home.tar, sdm.tar, and sdmconfig-xxx.cfg files are needed for SDM to run.

Reference:

http://www.cisco.com/en/US/products/sw/secursw/ps5318/prod_installation_guide09186a00803e4727.html

QUESTION 182:

You wish to see if router CK1 is capable of supporting SDM. What is the minimum IOS release that supports SDM?

- A. 11.2
- B. 12.0
- C. 12.1
- D. 12.2
- E. 6.1

Answer: D

Explanation:

SDM was first available in IOS 12.2. More specifically, SDM was initially compatible with the CiscoIOS images listed in the table below:

Table 1 SDM-Supported Routers and Cisco IOS Versions

SDM-Supported Routers	SDM-Supported Cisco IOS Versions
Cisco 831 and 837	• 12.2(13)ZH or later
Cisco 836	• 12.2(13)ZH or later
Cisco 1701	• 12.2(13)ZH or later
Cisco 1711 and 1712	• 12.2(15)ZL or later
Cisco 1710, 1721, 1751, 1751-v, 1760, and 1760-v	• 12.2(13)ZH or later
Cisco 2610XM, 2611XM, 2620XM, 2621XM, 2650XM, 2651XM, and 2691	• 12.2(11)T6 or later
Cisco 3640, 3661, and 3662	• 12.2(11)T6 or later
Cisco 3620	• 12.2(11)T6 or later
Cisco 3640A	• 12.2(13)T3 or later
Cisco 3725 and 3745	• 12.2(11)T6 or later
Cisco 7204VXR and 7206VXR	• 12.3(2)T or later
Cisco 7301	• 12.3(2)T or later

Reference:

http://www.cisco.com/en/US/products/sw/secursw/ps5318/prod_release_note09186a00801e7fef.html

QUESTION 183:

Choose the command that you will advise the new Certkiller trainee technician to use to verify that SDM has been installed on a Cisco router.

- A. show manager
- B. show version
- C. show flash
- D. show sdm
- E. show running-config

Answer: C

Explanation:

The quickest test is to connect your PC to the lowest-numbered Ethernet port with a cross-over cable and browse to `http://<router ip-address>` and see if Cisco SDM launch point is present on the resulting web page. If you have a Cisco 83x, 1701, 1710, 1711, or 1712 router, configure the PC to obtain an IP address automatically. If you have any other supported router, configure the PC with the static IP address 10.10.10.2.

Alternatively, you can use the CLI to check that the Cisco SDM files are present in the router Flash memory: enter `show flash` and look for the Cisco SDM file set: `sdm.tar`, `sdm.shtml`, `sdmconfig-xxxx.cfg`. If the files are present, then confirm that the router configuration is set to support Cisco SDM.

QUESTION 184:

Which of the following represents the two files that are necessary to run SDM on a new Certkiller Cisco router? (Select two)

- A. `secure.shtml`
- B. `sdm.shtml`
- C. `sdm.exe`
- D. `sdm.tar`
- E. `home.tar`
- F. `index.htm`

Answer: B, D

Explanation:

Issue the "show flash" command on Cisco routers to ensure that SDM has been installed. The SDM files that will be visible from this command are the `sdm.tar`, `sdm.shtml`, and `sdmconfig.cfg`. All of these files are necessary to run the SDM on the router.

Reference: CCSP Self-Study Securing Cisco IOS Networks, Cisco Press, John F Roland, Page 541

QUESTION 185:

Cisco Security Device Manager is running on a new Certkiller router. Select the maximum number of routers SDM can manage simultaneously?

- A. 1
- B. 5
- C. 50
- D. 100
- E. 500
- F. 1000
- G. Determined by router model

Answer: A

Explanation:

Cisco Router and Security Device Manager (SDM) is a web-based configuration tool that allows you to configure LAN and WAN interfaces, routing, Network Admission Control (NAC), Network Address Translation (NAT), firewalls, Intrusion Prevention System (IPS), Virtual Private Networks (VPNs), and other features on a single router. SDM is used as an application used to manage each router individually.

QUESTION 186:

You need to configure a new Certkiller router to support management via HTTP. Choose the two commands that are used to enable the router's HTTP server for AAA. (Choose two.)

- A. http server
- B. ip http server
- C. enable ip http server
- D. http authentication aaa
- E. http server authentication aaa
- F. ip http authentication aaa

Answer: B, F

Explanation:


In Cisco IOS(r) Software Release 11.2, a feature to manage the router through HTTP was added. The ip http authentication command enables you to specify a particular authentication method for HTTP server users. The HTTP server uses the enable password method to authenticate a user at privilege level 15. The ip http authentication command now lets you specify enable, local, TACACS, or authentication, authorization, and accounting (AAA) HTTP server user authentication. In addition to this command, the "ip http server" command is needed to enable the http service on the router.

Reference:

http://www.cisco.com/en/US/tech/CK59/technologies_configuration_example09186a0080178a51.shtml#local

QUESTION 187:

The following wizard was seen on a Certkiller router's web management portal.



Referring to the LAN Wizard screen shown above, how many bits would you input to configure this host for a subnet consisting of two hosts on subnet 172.26.26.0?

- A. 3
- B. 4
- C. 24
- D. 30
- E. 128
- F. 255

Answer: D

Explanation:

For any given subnet that supports only two hosts, the subnet mask of 255.255.255.252 (/30) should be used. This will provide for a network of 4 IP addresses, with only two usable IP addresses available for end hosts. Using the wizard, the number 30 should be input for the bits used in the subnet mask.

QUESTION 188:

Which of the following URLs is used to securely access SDM on a Certkiller router with an IP address of 10.0.5.12?

- A. <https://10.0.5.12/flash/sdm.tar>
- B. <https://10.0.5.12/flash/sdm.html>
- C. <https://10.0.5.12/flash/sdm.shtml>
- D. <https://10.0.5.12/flash/sdm>
- E. <http://10.0.5.12/flash/sdm.shtml>

Answer: C

Explanation:

SDM is stored in the router Flash memory. It is invoked by executing an HTML file in the router archive, which then loads the signed SDM Java file. To launch SDM:

Step 1 From your browser, type in the following universal resource locator (URL):

<https://<router IP address>>

https://... specifies that the Secure Socket Layer (SSL) protocol be used for a secure connection.

Example: https://10.0.5.12/flash/sdm.shtml

QUESTION 189:

A network administrator is using SDM to manage one of the Certkiller routers. Which one of the following actions is used to send SDM generated commands to the target router?

- A. Refresh
- B. Save
- C. Deliver
- D. Download
- E. Copy-config

Answer: C

Explanation:

If you are working in advanced mode of the SDM, you must save your work by clicking the Deliver button on the SDM toolbar. The Deliver window allows you to preview the commands that you are sending to the router, and allows you to specify that you want the commands saved to the router's startup configuration.

QUESTION 190:

You are managing a Certkiller router via the SDM web interface. Which of the following actions is used to prevent newly configured SDM commands from being sent to a target router?

- A. Delete
- B. Remove
- C. Undo
- D. Clear-commands
- E. Refresh

Answer: E

Explanation:

The refresh option reloads configuration information from the router. If there are any undelivered commands, SDM displays a message window telling you that if you refresh, you will lose undelivered commands. If you want to deliver the commands, click No in the window, and then click Deliver on the SDM toolbar.

Reference:

http://www.cisco.com/en/US/products/sw/secursw/ps5318/products_user_guide_chapter09186a00803d5ab7.htm

QUESTION 191:

EXHIBIT (Incomplete):




Refer to the Cisco Router and Security Device Manager page in the exhibit. What would be the best result of clicking the "Launch the selected task" button in the VPN configuration screen?

- A. to start the GRE site-to-site VPN connection configuration
- B. to edit the site-to-site VPN connection
- C. to start the security audit
- D. to start the Easy VPN Server configuration
- E. to start the default site-to-site VPN connection configuration
- F. to start the Easy VPN Remote configuration

Answer: E

QUESTION 192:**SIMULATION**

The Certkiller network is shown in the following exhibit:



You have been assigned to configure CBAC on a branch router for Certkiller .com. One router from your oil company is named Dallas. The topology is pictured in the graphic. The corporate router has already been configured. All that is left to do is to configure CBAC on the local router to inspect Web and FTP traffic to the corporate server and to allow ICMP from any source to any destination and EIGRP from the outside interface of the corporate router to the outside interface of the branch

router but block everything else. Access control list 100 has already been built and applied to Fa0/0. Do not modify access control list 100. You should add no more than three access control list statements. Logging has been enabled but you must configure the SYSLOG server address. The enable password for the router is cisco. The following passwords have been assigned to the Dallas router:

Console password: california

Vty lines 0-4 password: state

Answer:

Explanation:

```
router> enable
```

```
router# configure terminal
```

```
router(config)# logging 10.0.2.12
```

```
router(config)# no ip inspect alert-off
```

```
router(config)# ip inspect audit-trail
```

```
router(config)# ip inspect name FWRULE http timeout 300
```

```
router(config)# ip inspect name FWRULE ftp timeout 300
```

```
router(config)# access-list 101 permit icmp any any
```

```
router(config)# access-list 101 permit eigrp host 172.30.2.1 host  
172.30.2.2
```

```
router(config)# access-list 101 deny ip any any
```

```
router(config)# interface FastEthernet 0/1
```

```
router(config-if)# ip inspect FWRULE out
```

```
router(config-if)# ip access-group 101 in
```

```
router(config-if)# end
```

Note: there is no ability to use "copy running-config startup-config" or "write memory", so each solution should use the "end" command in config mode to save the current configuration.

QUESTION 193:

An authentication attempt to a Cisco Secure ACS for Windows server failed, yet no log entries are in the reports. What are two possible causes of this problem?


(Choose two.)

- A. user is not defined
- B. user belongs to the wrong group
- C. CSAUTH service is down on the Cisco Secure ACS server
- D. Password has expired
- E. User entered an incorrect password
- F. Communication path between the NAS and Cisco Secure ACS server is down

Answer: C, F

Topic 1, Certkiller .com, Scenario

Network topology exhibit



Simulation output: *** Missing ***

You work as a network technician at Certkiller .com. Your boss, miss Certkiller, has ordered you to troubleshoot a Certkiller branch of network. You need to answer some questions regarding this network using the network topology and the output you retrieve from Cisco devices on the network.

Topic 1, Certkiller .com (4 Questions)

QUESTION 194:

Please refer to the Certkiller .com scenario available in the iPad document.
Where are the signatures being loaded from?

- A. NVRAM
- B. Flash
- C. TFTP server
- D. Built-in signatures
- E. There are no signatures

Answer:

QUESTION 195:

Please refer to the Certkiller .com scenario available in the iPad document.
Which interface is the rule applied to.

- A. There is no rule.
- B. Fa0/0
- C. Fa0/1
- D. Fa0/2
- E. S0/0
- F. S0/1
- G. S0/2

Answer:

QUESTION 196:

Please refer to the Certkiller .com scenario available in the iPAD document.
How many signatures are loaded?

- A. 0
- B. 1
- C. 81
- D. 82
- E. 83
- F. 100
- G. 1000
- H. 10000
- I. An infinite number

Answer:

QUESTION 197:


Please refer to the Certkiller .com scenario available in the iPAD document.
How many total inactive signatures are there?

- A. 0
- B. 1
- C. 81
- D. 82
- E. 83
- F. 100
- G. 1000
- H. 10000
- I. An infinite number

Answer:

Topic 2: Certkiller .com #2, Scenario

Network topology exhibit:



```
router> enable
router# show ip ips configuration
Configured Config Locations: -none-
Last signature default load time: 18:46:50 UTC Jan 5 2007
Last signature delta load time: -none-
Last event action (SEAP) load time: -none-
IPS Auto Update is not currently configured
IPS fail closed is disabled
Fastpath ips is enabled
Quick run mode is enabled
Event notification through syslog is enabled
Event notification through SDEE is enabled
Total Active Signatures: 82
Total Inactive Signatures: 0
IPS Rule Configuration
IPS name test
IPS Category CLI is not configured
Interface Configuration Interface
FastEthernet0/1
Inbound IPS rule is test
Outgoing IPS rule is not set
router# show ip ips signatures
Builtin signatures are configured
Signatures were last loaded from flash:128MB.sdf
Cisco SDF release version 128MB.sdf v4
Trend SDF release version V0.0
[ more output deleted ]
```

Topic 2: Certkiller .com #2 (4 Questions)

QUESTION 198:

Note: Please refer to the Certkiller .com scenario available in the iPAD document.

From where are the signatures being loaded from?

- A. Built-in signatures
- B. TFTP server
- C. Flash
- D. NVRAM

Answer: C

Explanation: Refer to the "show ips signatures" command output.

QUESTION 199:

Note: Please refer to the Certkiller .com scenario available in the iPAD document.
How many signatures are loaded?


- A. 0
- B. 82
- C. 100
- D. 1000

Answer: B

Explanation: Refer to the "show ip ips configuration" command output.

QUESTION 200:

Note: Please refer to the Certkiller .com scenario available in the iPAD document.



How many inactive signatures are loaded?

- A. 0
- B. 82
- C. 100

D. 1000

Answer: A

Explanation: Refer to the "show ip ips configuration" command output.

QUESTION 201:

Note: Please refer to the Certkiller .com scenario available in the iPAD document.
To which interface is the rule applied to?

- A. S0/0
- B. S0/1
- C. Fa0/0
- D. Fa0/1

Answer: D

Explanation: Refer to the "show ip ips configuration" command output.